

The Well-X1 system combines city-like water pressure utilizing an existing pump. It's the perfect alternative to complicated, expensive and difficult to install VFD systems. Pre-assembled and ready-to-run, it's the ultimate combination of quality, savings and performance.



The VFD Alternative

- City-like water pressure from existing submersible or jet pumps.
- Maintains 10 psig differential for smooth, consistent flow.
- Pump does not run constantly which saves energy.

Well-X-Trol® Well Tank

- Features include high strength steel, 150 psig, Tuf-Kote™ HG, Turbulator and DuraBase stand.
- Provides supplemental storage for peak demands.
- 7 year warranty.



Guardian CP™ Digital Control

- Digital pressure gauge. Adjustable up to 80 psig.
- Real time system diagnostics.
- 2 year warranty.

Fast, Easy Installation

- Simple 4-wire setup.
- Auto adjusts to 115 or 230 VAC.
- Remains idle if wired improperly.
- Pre-assembled with:
 - Guardian CP Control
 - Compression Fittings
 - Decorative Cap
 - Relief Valve
 - Mounting Bracket
 - Drain Assembly
 - Brass Tank Tee
 - Press Sleeves
 - Copper Tubing



Pump Protection



RAPID CYCLE:
Alerts user before pump damage occurs.




LOW WATER CUTOFF:
Shuts off pump when below 10 psig; automatically restarts every 60 minutes.



IMPROPER VOLTAGE:
Shuts off pump; automatically restarts with proper voltage.

Comparable Pressure Performance



1. Well-X1 System: Guardian CP set at 40/50 psig with 1/2 HP submersible pump and 44 gal. well tank.
2. Variable Speed System: 3/4 Variable Speed pump set at 47 psig with a 2 gal. in line tank.