

# SMF IC620-5 LOW DRAW BOOSTER COMBO

SYSTEM PART: #66-0625LFM  
 REPLACEMENT CARTRIDGE KIT: #108-025S  
 RATED BOOSTED CAPACITY (GALLONS): CHLORINE : 100,000  
 CHLORAMINE \*: 30,000  
 RATED UN-BOOSTED CAPACITY (GALLONS): SCALE: 75,000  
 MIN./MAX. PRESSURE: 40- 125 PSI  
 MIN./MAX. TEMP.: 40°- 100° F  
 INLET/OUTLET SIZE: 3/8" BARB STANDARD  
 SHIPPING WEIGHT: 65 LBS.  
 DIMENSIONS (W/D/H): 18.6/14/45.5"

**WATER BOOSTER DATA:** McCANN'S 2 GALLON, 115V, 60 HZ.  
 INLET PRESSURE: MINIMUM: 20 PSI  
 OUTLET PRESSURE: 80-100 PSI  
 FLOW RATE: MAXIMUM: 100 GPH  
 OZ. AVAILABLE FROM 80 - 100 PSI: 21 Oz.  
 TOTAL RESERVE AVAILABLE AT 40 PSI: 93 Oz.



## FOUNTAIN/ICE APPLICATION

FOR: CHLORINE, CHLORAMINE, SEDIMENT,  
 THMS, ORGANICS, TANNINS, BAD TASTE,  
 SCALE AND ODOR REDUCTION

VOLUME: HIGH VPO

TO 6000 GALLONS OF SYRUP FOR  
 CHLORINE & CHLORAMINE  
 REDUCTION

### SPECIFIED TO:

- IMPROVE TASTE OF FOUNTAIN BEVERAGES
- PROVIDE SAFE, CLEAN INGREDIENT WATER
- REDUCE CHLORINE, CHLORAMINE, BAD TASTES AND ODORS, TOTAL ORGANIC COMPOUNDS, TANNINS AND TRIHALOMETHANES
- INCREASE FOUNTAIN SALES
- INCREASE CARBONATION

### FILTER BENEFITS:

- ONE FILTER CAN DO IT ALL: DIRT REDUCTION, CHEMICAL REDUCTION AND CHLORAMINES REDUCTION! NO PRE-FILTER REQUIRED!
- THE FIRST JUMBO SANITARY FILTER ON THE MARKET!
- NYLON CONSTRUCTION TO WITHSTAND HIGH PRESSURE!
- FILTER PERFORMANCE GUARANTEE!
- 40 TIMES MORE DIRT HOLDING CAPACITY THAN CONVENTIONAL CARBON BLOCK FILTERS AND OTHER POLYPROPYLENE SEDIMENT FILTERS!
- 30 TIMES THE CHLORAMINE REDUCTION OF A CONVENTIONAL CARBON BLOCK!
- LOW PRESSURE DROP!
- MODULAR FILTER DESIGN FOR UP TO 50% LESS INSTALLATION TIME!

### TECHNOLOGY:

- ULTRA HIGH POROSITY CARBON WITH MICRO-STRUCTURE
- SILIPHOS SCALE INHIBITOR

### APPLICATIONS:

- 1 TO 2 CARBONATORS
- FOUNTAIN AND MULTIUSE APPLICATION SUCH AS COFFEE, TEA AND ICE

\* Independently tested by an E.P.A. approved laboratory to ANSI/NSF Standard 42 & 53 specifications for the reduction of Cyst, Particulate Class I, Chlorine, Chloramine, Taste and Odor.



System has been tested and certified by NSF International against ANSI/NSF Std. 53 and ANSI/NSF Std. 42. Please visit [www.nsf.org](http://www.nsf.org) for specifications. Do not use with water that is microbiologically unsafe or of unknown quality.

**selecto**

3980 LAKEFIELD COURT, SUWANEE, GA 30024 USA  
 800-635-4017 • 678-475-0799 • [WWW.SELECTOINC.COM](http://WWW.SELECTOINC.COM)

© 2007 Selecto Scientific, Inc. • All Rights Reserved.

Rev. 12-04-07