





Contaminants Reduced:



Residential/Commercial Filtration Applications

Standard Features

- Manufactured in South Korea
- Formally NP-SQC706
- Replacement filter cartridge for the Water Factory Systems 47-55706G2
- Used in the SQC3, Scale Guard SGLP-RO #55706-21 and FlashGARD HP RO #55706-20
- Reduces sediment, dirt and rust
- Quick change design for easy installation
- Also compatible with Cuno® 55706-11, 55706-10, 55706-08, and 56136-03; Essential® F06G2; Shaklee 61029-31; Water Factory Systems 47-55706G2, 47-55706CM

Product Specifications

Micron Rating (Nominal)

5 microns

Flow Rate

0.6 gpm

Operating Temperature

40 to 100°F (4.4 to 37.8°C)*

Max Operating Pressure

30-120 psi

Change Frequency

6 to 12 months

Capacity

1500 Gallons

Materials of Construction

Filter Media: Polypropylene

Outer Shell:

Distributed



2299 Ridge Rd., Greenville, SC P: 888.859.1188 · F: 864.284.1819 NeoLogicSolutions.com · Info@NeoLogicSolutions.com **Ouestions?**

Ask our Service Representatives at: 888.859.1188 Mon.-Fri. 8a-8p, Sat 8:30a-4:30p EST.

^{*}Temperature ratings vary and depend on pressure and time under load