

General Purpose, Single Phase (NEMA Service Factor), Dripproof

Features:

- Ball bearings, mechanically locked on shaft end (excludes 5K models)
- NEMA Service Factors
- Heavy gauge steel frame and base
- Capacitor start design for high starting torque
- Capacitor start/capacitor run design for higher efficiency, as noted
- UL Recognized and CSA Certified



C-Face Footed (Rigid Base)

| HP | RPM | VOLTS | FRAME | OVER LOAD | CAT. NO. | MODEL NO. | STOCK | LIST PRICE | MULT. SYMB. | F.L. AMPS | WT. | "C" DIM. | FOOT NOTES |
|-----|------|-----------------|-------|-----------|----------|---------------|-------|------------|-------------|-------------------|-----|----------|------------|
| 1/4 | 1800 | 115/208-230 | 56C | AUTO | K234 | 056C17D2114 | | \$217 | F1 | 5.0/2.3-2.5 | 18 | 10.30 | |
| 1/3 | 1800 | 115/208-230 | 56C | AUTO | K235 | 056C17D2115 | ✓ | \$252 | F1 | 6.4/3.0-3.2 | 18 | 10.30 | |
| | 1800 | 100-120/200/240 | 56C | MANUAL | E250 | 5KCR46JN0083Y | ✓ | \$303 | F1 | 4.0-3.8/2.0-1.9 | 24 | 10.77 | d,ES,1,6,8 |
| | 1800 | 100-120/200/240 | 56C | AUTO | E252 | 5KCR46JN0083X | ✓ | \$252 | F1 | 4.0-3.8/2.0-1.9 | 23 | 10.77 | ES,1,6,8 |
| 1/2 | 1800 | 100-120/200-240 | 56C | AUTO | E261 | 5KCR46MN0090X | ✓ | \$293 | F1 | 5.8-5.6/2.9-2.8 | 27 | 10.77 | ES,1,6,8 |
| | 1800 | 100-120/200-240 | 56C | MANUAL | E259 | 5KCR46MN0090Y | | \$351 | F1 | 5.8-5.6/2.9-2.8 | 27 | 10.77 | ES,1,6,8 |
| 3/4 | 1800 | 100-120/200-240 | 56C | AUTO | E270 | 5KCR49PN0095X | ✓ | \$356 | F1 | 9.0-8.8/4.5-4.4 | 31 | 11.37 | ES,1,6,8 |
| | 1800 | 100-120/200-240 | 56C | MANUAL | E268 | 5KCR49PN0095Y | ✓ | \$405 | F1 | 9.0-8.8/4.5-4.4 | 30 | 11.37 | ES,1,6,8 |
| 1 | 1800 | 100-120/200-240 | 56C | MANUAL | EG277 | 5KCR48UN0102Y | | \$576 | F1 | 11.8-11.4/5.9-5.7 | 40 | 12.65 | ES,1,6,8 |
| 2 | 3600 | 115/208-230 | 56C | MANUAL | C1269 | 5KC49SN2537Y | ✓ | \$600 | F1 | 15.6/8.8-7.8 | 36 | 11.34 | |
| 3 | 3600 | 208-230 | 56C | MANUAL | C1270 | 5KC492N2539Y | ✓ | \$733 | F1 | 13.0-12.0 | 41 | 12.84 | |