

Bulkhead Union

Pressure Ratings			
	< 5/16"	3/8"	1/2"
33 °F	290 psi	232 psi	203 psi
68 °F	290 psi	232 psi	203 psi
150 °F	232 psi	203 psi	116 psi

Torque Allowance					
Thread Size	1/8"	1/4"	3/8"	1/2"	3/4"
Max Torque	1.1 ft lbs	1.1 ft lbs	2.2 ft lbs	2.2 ft lbs	2.9 ft lbs

MODEL	ΦD1	ΦD2	T	L	E	A	B1	B2	H1(Hex)	H2(Hex)	WEIGHT(g)
ABU44M	04	04	M15x1.5	32.4	6.5	8.1	14.7	14.7	17	18	6.9
ABU64M	06	04	M17x1.5	35.5	7	9.4	16.1	14.7	19	21	9.8
ABU66M	06	06	M17x1.5	35.7	7	9.4	16.1	16.1	19	21	9.6
ABU86M	08	06	M20x1.75	38.1	8	9.4	17.5	16.1	21	25.5	14.3
ABU88M	08	08	M20x1.75	38.5	8	9.4	17.5	17.5	21	25.5	14
ABU1010M	10	10	M24x1.75	42.2	8.5	11.1	20.1	20.1	24	28.5	19.5
ABU1212M	12	12	M27x2.0	51.4	9	16.4	24.7	24.7	27	31	28.2

