# NP-OVF001 Oasis VersaFilter Compatible Water Filter





# **Contaminants Reduced:**

- Chlorine Taste and Odor
- Cyst
- Lead
- Sediment, Dirt and Rust







Tested and certified to NSF Standard 42 and 53



## Residential/Commercial Filtration Applications

### **Standard Features**

- Manufactured in the USA
- Spun polypropylene prefilter wrap
- Double o-ring seal prevents bypass
- Eco-friendly coconut shell carbon block filter media
- Shut-off valve engages automatically when filter is installed or removed
- Cartridge is sealed, preventing the potential for introducing bacteria through handling
- Automatic shut-off inside filter head
- Used in Oasis® Barrier-Free Versacooler II and split level models with Versafilter System PFAC, PF8AC, PF8ACEE, PF8ACSL, PF8ACSL, PF8ACSLEE, PRF8ACSLEE, PFACSL, or PRFACSL

## **Product Specifications**

#### **Dimensions**

2-1/2" diameter x 10"

#### Filter Media

Coconut shell carbon block

#### **Capacity**

1250 gallons for lead, 2500 gallons for chlorine reduction

#### **Operating Temperature**

35-100°F (2-38°C)

#### **Maximum Operating Pressure**

125 psig (8.6 bar)

#### **Maximum Flow Rate**

0.5 gpm

#### **Micron Rating (Nominal)**

1 micron

#### **Change Frequency**

6 months

#### **WARNING:**

Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.



9450 SW Gemini Dr, ECM #83358, Beaverton, OR 97008 Tel 855.896.3525 · Fax 866.409.9622

www.neologicsolutions.com · info@neologicsolutions.com

STUART, FL · BEAVERTON, OR · GREENVILLE, SC · SAN DIEGO, CA

#### QUESTIONS?

Ask one of our Service Representatives: Mon-Fri 8a-8p, Sat 8:30a-4:30p EST

