Couplings

EMT Steel Set Screw Connecters and Couplings



Couplings - Steel



| Part No. | Mfg. No. | Size | Pkg. Qty. |
|----------|----------|--------|-----------|
| 0700205 | 2022-8 | 1/2" | 25 |
| 0700206 | 2023-8 | 3/4" | 20 |
| 0700207 | 2024-8 | 1" | 10 |
| 0700208 | 2025 | 1-1/4" | 5 |
| 0700209 | 2026 | 1-1/2" | 1 |
| 0700210 | 2028 | 2" | 1 |

EMT Steel Compression Connecters and Couplings Couplings - Steel



| Part No. | Mfg. No. | Size | Pkg. Qty. |
|----------|----------|--------|-----------|
| 0703602 | 2922-8 | 1/2" | 1 |
| 0703603 | 2923-8 | 3/4" | 1 |
| 0703604 | 2924-8 | 1" | 1 |
| 0703605 | 2925 | 1-1/4" | 5 |
| 0703606 | 2926 | 1-1/2" | 1 |
| 0703607 | 2928 | 2" | 1 |

EMT Die Cast Set Screw Connecters, **Couplings & Offsets**

Applications

- RACO® die-cast set screw couplings provide concrete-tight connections when taped
- . RACO® set screw couplings are suitable for applications above 600v



| Part No. | Mfg. No. | Size | Pkg. Qty. |
|----------|----------|--------|-----------|
| 0700160 | 2622 | 1/2" | 1 |
| 0700161 | 2623 | 3/4" | 1 |
| 0700162 | 2624 | 1" | 1 |
| 0700163 | 2625 | 1-1/4" | 25 |
| 0700164 | 2626 | 1-1/2" | 10 |
| 0700165 | 2628 | 2" | 5 |

EMT Die Cast Compression Connecters and Couplings & Offsets Couplings

| | | | \sim |
|----------|----------|--------|-----------|
| Part No. | Mfg. No. | Size | Pkg. Qty. |
| 0700235 | 2822 | 1/2" | 1 |
| 0700236 | 2823 | 3/4" | 1 |
| 0700237 | 2824 | 1" | 1 |
| 0700238 | 2825 | 1-1/4" | 25 |
| 0700239 | 2826 | 1-1/2" | 10 |
| 0700240 | 2828 | 2" | 5 |

Rigid and IMC Fittings Steel -**Set Screw Connecters** and Couplings





| Part No. | Mfg. No. | Size | Pkg. Qty. | |
|----------|----------|--------|-----------|--|
| 0700190 | 3022 | 1/2" | 1 | |
| 0700191 | 3023 | 3/4" | 1 | |
| 0700192 | 3024 | 1" | 1 | |
| 0700193 | 3025 | 1-1/4" | 1 | |
| 0700194 | 3026 | 1-1/2" | 1 | |
| 0700195 | 3028 | 2" | 1 | |

Rigid and IMC Fittings Die Cast

90° Handy Ells Threaded **Couplings Die Cast Zinc Features**



 $(U_{\rm I})$

· Gasket and cover included

Applications

- · For use with threaded rigid/IMC conduit to couple two ends of rigid/IMC conduit
- · Use handy ells when bending conduit is

| not practical | | | \circ |
|---------------|----------|------|-----------|
| Part No. | Mfg. No. | Size | Pkg. Qty. |
| 0703639 | 2652 | 1/2" | 10 |
| 0703640 | 2653 | 3/4" | 5 |
| 0703641 | 2654 | 1" | 1 |

Rigid and IMC Fittings Malleable Iron - Three-Piece Couplings **Features**


- · All steel/malleable construction insures mechanical protection of the raceway
- · All components are zinc electro plated for corrosion protection

Applications

- · For use with threaded rigid/IMC conduit
- · Use three-piece couplings to couple conduit ends when the conduit cannot be turned
- RACO® three-piece couplings provide concrete-tight connections







Nipples

Offset Nipples and **Uninsulated Nipples**

Die Cast Zinc - 3/4" Offset **Feature**



· Rugged metallic construction provides mechanical protection for the conductors

Applications

· For use when connecting two boxes or panels when the knockouts are not in line.



| | | \sim |
|----------|----------|----------|
| Part No. | Mfg. No. | Diameter |
| 0700618 | 1452 | 1/2" |
| 0700619 | 1453 | 3/4" |
| 0700620 | 1454 | 1" |
| 0700621 | 1/155 | 1_1//!" |

Offset Nipples and **Uninsulated Nipples**

Die Cast Zinc - Uninsulated



| Part No. | Mfg. No. | Diameter | Ī |
|----------|----------|----------|---|
| 0700630 | 1662 | 1/2" | Ξ |
| 0700631 | 1663 | 3/4" | |
| 0700632 | 1664 | 1" | |
| 0700633 | 1665 | 1-1/4" | _ |
| 0700634 | 1666 | 1-1/2" | _ |
| 0700635 | 1668 | 2" | |

Washers

Liquidtight Conduit Connectors Steel -**Sealing Washers**



RACO

Feature

· Steel ring is zinc electro plated for added corrosion protection

Applications

• For use whenever a positive seal is required between the shoulder of a fitting and an enclosure



| | | \sim |
|----------|----------|--------|
| Part No. | Mfg. No. | Size |
| 0703658 | 2454-8 | 1" |
| 0703659 | 2455 | 1-1/4" |
| 0703660 | 2456 | 1-1/2" |
| 0703661 | 2458 | 2" |

Reducing Washers Features

- All steel construction provides installation integrity
- · Zinc electroplated for added corrosion protection

Applications

For use when a raceway is smaller in trade size than the trade size of the knockout it is intended to enter.



| Part No. | Mfg. No. | Size |
|----------|----------|-----------------|
| 0700646 | 1365 | 3/4" - 1/2" |
| 0700647 | 1366 | 1" - 1/2" |
| 0700648 | 1367 | 1" - 3/4" |
| 0700649 | 1368 | 1-1/4" - 1/2" |
| 0700650 | 1369 | 1-1/4" - 3/4" |
| 0700651 | 1370 | 1-1/4" - 1" |
| 0700652 | 1371 | 1-1/2" - 1/2" |
| 0700653 | 1372 | 1-1/2" - 3/4" |
| 0700654 | 1373 | 1-1/2" - 1" |
| 0700655 | 1374 | 1-1/2" - 1-1/4" |
| 0700656 | 1375 | 2" - 1/2" |
| 0700657 | 1376 | 2" - 3/4" |
| 0700658 | 1377 | 2" - 1" |
| 0700659 | 1378 | 2" - 1-1/4" |
| 0700660 | 1379 | 2" - 1-1/2" |
| 0700663 | 1380 | 2-1/2" - 1" |
| 0700664 | 1381 | 2-1/2" - 1-1/4" |
| 0700665 | 1382 | 2-1/2" - 1-1/2" |
| 0700666 | 1383 | 2-1/2" - 2" |

Lock Nuts

Rigid and IMC Fittings Steel/Malleable Iron -Locknuts

Features

- All steel/malleable construction insures mechanical protection
- · Zinc electro plated for corrosion protection



For use on threaded rigid/ IMC conduit.



HUBBELL

RACO

| iivio conduit. | | \sim |
|----------------|----------|---------------------|
| Part No. | Mfg. No. | Thread Size |
| 0700595 | 1002 | 1/2" - 14 NPT |
| 0700596 | 1003 | 3/4" - 14 NPT |
| 0700597 | 1004 | 1" - 11-1/2 NPT |
| 0700598 | 1005 | 1-1/4" - 11-1/2 NPT |
| 0700599 | 1006 | 1-1/2" - 11-1/2 NPT |
| 0700600 | 1008 | 2" - 11-1/2 NPT |
| 0700601 | 1010 | 2-1/2" - 8 NPT |
| 0700602 | 1012 | 3" - 8 NPT |
| 0700603 | 1014 | 3-1/2" - 8 NPT |

