



The Challenge:

Excess chlorine can oxidize parts and fittings, and excessive hardness can form scale in your espresso equipment, reducing service life and causing bitter-tasting beverages.

The Solution:

3M™ Water Filtration Products containing ion exchange resin media can help reduce hardness and improve espresso beverage quality without the need for a drain, electrical connection or salt regeneration.

Water 98% of an espresso

Espresso Water Filtration Systems

Espresso					
Model/Part	Replacement Cartridge	Flow Rate (GPM)	Capacity (Gals)	Micron	Reduction Claims
ESP124-T 5634802	PS124	0.5	1,100 grains	1.0	Softening, chlorine taste and odor
SGP124BN-T 5634801	P-124BN	0.5	422.6 gals @ 10.5 gpg	1.0	Hard scale, chlorine taste and odor
SGP165BN-T 5633201	P-165BN	1.0	719 gals @ 9.0 gpg	0.5	Hard scale, chlorine taste and odor
SGP195BN-T 5633301	P-195BN	1.0	1,200 gals @ 9.0 gpg	1.0	Hard scale, chlorine taste and odor

ScaleGard™ Bl	caleGard [™] Blend Series of Cartridges			
Model/Part	Flow Rate (GPM)	Capacity (Gals)*	Reduction Claims	
B145-CLS 5629701	0.5	530 gals @ 11 gpg	Hard scale, chlorine taste and odor, chloramines	
B165-CLS 5630401	0.5	749 gals @ 11 gpg	Hard scale, chlorine taste and odor, chloramines	
B195-CLS 5630501	0.5	1,249 gals @ 11 gpg	Hard scale, chlorine taste and odor, chloramines	

^{*}Based on standard blend for coffee machines without steam operation.

Model/Part	Description	
8 H3-NPT Head 8240807	Valve-in-head assembly with blend adjustment and NPT fittings	
8 H3M-NPT Head 8240809	Valve-in-head assembly with blend adjustment, Local monitor and NPT fittings	
H3WM-NPT ead/6240810	Valve-in-head assembly with blend adjustment, Wi-Fi monitor and NPT fittings	





ESP Series Softening and ScaleGard™ Pro Series Products Capacity Gallons (Liters) Inlet Hardness (ppm/gpg) ESP124-T SGP124BN-T SGP165BN-T SGP195BN-T 50 (3) 367 (1,388) 1,525 (5,773) 2,157 (8,164) 3,595 (13,607) 60 (4) 275 (1,041) 1,271 (4,811) 1,798 (6,804) 2,996 (11,339) 100 (6) 183 (694) 763 (2,886) 1,079 (4,082) 1,798 (6,804) 140 (8) 138 (520) 545 (2,062) 770 (2,916) 1,284 (4,860) 180 (11) 100 (379) 424 (1,604) 599 (2,268) 999 (3,780) 899 (3,402) 200 (12) 92 (347) 381 (1,443) 539 (2,041) 240 (14) 79 (297) 318 (1,203) 449 (1,701) 749 (2,835) 280 (16) 69 (260) 272 (1,031) 385 (1,458) 642 (2,430)

ScaleGard™ Pro Series Products (SGP124BN-T, SGP165BN-T and SGP195BN-T) reduce hardness from water to help reduce scale, but also feature built-in non-adjustable blend mechanisms to allow some hardness to remain in the product water, deemed important for flavor of the espresso.

238 (902)

212 (802)

191 (722)

337 (1,276)

300 (1,134)

270 (1,021)

562 (2,126)

499 (1,890)

449 (1,701)

ESP Series Products do not feature a built-in blend mechanism.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

320 (19)

360 (21)

400 (23)

58 (219)

52 (198)

48 (181)

Warranty, Limited Remedy and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.



3M Purification Inc. 400 Research Parkway Meriden, CT 06450

Phone 1-866-990-9785 WW 1-203-237-5541 Fax 1-203-238-8701 Web 3Mfoodservice.com

Clear things up at 3MFoodService.com

3M and ScaleGard are trademarks of 3M Company. Please recycle. Printed in USA. © 3M 2018. All rights reserved. 70-2016-0007-2