

Neo-Pure® IL2510-CTOCL-4Q

Inline Carbon Block 1 Micron CTO, Cyst and Lead Reduction



Important Notice: Read this Performance Data Sheet and compare the capabilities of this unit with your actual water treatment needs. It is recommended that, before purchasing a water filter unit, you have your water supply tested to determine your actual water treatment needs.

Performance Data Summary:

| Parameter | US EPA MCL | Influent Challenge | Effluent Average | Effluent Maximum | Percent Reduction Average | Percent Reduction Minimum |
|------------------|------------------|--------------------|------------------|------------------|---------------------------|---------------------------|
| Chlorine | — | 2.22 ppm | <0.1 | <0.1 | >99 | >75 |
| Cyst | 99.95% Reduction | 104,457 Particles | < 1 | <1 | 99.99% | — |
| Lead High 8.5 pH | 15 | 150 ppb | 1 ppb | >1 | 99% | 90 |
| Lead Low 6.5 pH | 15 | 160 ppb | 1 ppb | >1 | 99% | 90 |

Tested according to NSF Standard 42 for aesthetic effects and Standard 53 for health effects (tested using flow rate = 0.5 Gpm; pressure = 60 psig; ph = 7.5 _ 0.5; Temp. = 20_ 2.5_ C).

General Installation/Operation/Maintenance Requirements:

- Note flow direction of filter.
- Flush new cartridge with 5 gallons of water prior to use and check for leaks. If leaks occur, check tightness of tubing and fittings. If leaks persist, discontinue use and call your supporting dealer.
- Replace cartridge when rated capacity is reached, or when flow becomes too slow.
- Install in compliance with state and local laws and regulations.

Special Notices:

- The contaminants or other substances removed or reduced by this water treatment system are not necessarily in your water.
- Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

Operating Specifications:

Dimensions: L = 10", OD = 2-1/2", 1/4" Quick Connect
Capacity: 1,250 Gallons Lead reduction
Flow Rate: 0.50 GPM (1.9 LPM)
Maximum Pressure: 125 PSIG
Temperature: 35-100° F (2-38° C)

For Use In:

Refrigerators
 Beverage Equipment
 Ice Makers
 Post RO
 Water Coolers
 Drinking Fountains
 Distillers

Distributed By:



2299 Ridge Rd., Greenville, SC
 P: 888.859.1188 · F: 864.284.1819
NeoLogicSolutions.com · Info@NeoLogicSolutions.com

All rights reserved. Manufacturer reserves the right to make changes without notice. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after unit. All company names are registered trademarks of their respective holders. USA Made. ©2018 NeoLogic Solutions, Greenville SC, 29607



Questions?

Ask our Service Representatives at:
 888.859.1188 Mon.-Fri. 8:30a-7p,
 Sat 8:30a-4:30p EST.