

IcePRO SERIES KPMF IPF610-PP Water Filtration

Single Manifold Part #:	KP-300-777	
Replacement Cartridge:	KPMF IPF610-PP	
		19'
	0 7 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8	

APPLICATIONS



- Volume: Low-Medium
- Optimal for <800 lb ice machine

DESIGNED TO

- Remove disinfectants and contaminants, providing high quality water to your ice machine
- Enhance guest satisfaction by improving ice quality and minimizing cloudiness
- Prolong equipment life by reducing scale and slime build-up
- Minimize pressure drop and reduce scale to boost ice production efficiency

PERFORMANCE

Chlorine Capacity	50,000 gal @ 5gpm
Chloramine Capacity	7,150 gal @ 1.7gpm*
Scale Reduction	Up to 50,000 gal @ 5gpm
Min./Max. Pressure	40 - 100 psi
Min./Max. Temp.	40°- 100°F
Inlet/Outlet Size	3/4" FNPT
Shipping Weight	15 lb
Dimensions (W/D/H)	14" x 9" x 19"

Performance may vary based on local water conditions *Tested by 3rd party laboratory to the NSF/ANSI Standard 42

FEATURES & BENEFITS

- Activated hollow carbon with NO binding agent delivers high capacities, high flow rates, and minimal pressure drop
- Engineered polymer construction for high durability and extended service life
- Modular design allows for easy capacity expansion
- Time released polyphosphate increases protection of equipment from scale build up



1.800.321.5022 www.KineticoPRO.com WaterCare@KineticoPRO.com



Tested and certified by NSF International against NSF/ANSI Standard 42 for the reduction of chlorine, particulate class I, and taste & odor.