WaterSentinel®



WSA-1

REFRIGERATOR REPLACEMENT FILTER







This filter should not be used with water that is microbiologically unsafe or of unknown quality, without adequate disinfection before and/or after the filter.

This filter has been tested by the manufacturer against ANSI/NSF Standard 42 for the reduction of Chlorine, Tastes and Odors.

This product is covered by the following US Patent: 8,216,463



This WSA-1 is Tested and Certified by NSF International against NSF/ANSI Standard 42 for materials and structural integrity requirements.

The following claim has not been tested and certified by NSF: "FITS IN PLACE OF"

ADVANCED FILTRATION TECHNOLOGY

This WaterSentinel® refrigerator water filter contains a compressed carbon block which provides tremendous capacity to remove and/or reduce impurities and sediment that may be present in your drinking water. The carbon block has millions of active sites on it's surface and within the structure which can absorb impurities like a sponge, and can adsorb and hold other types of impurities on it's surface like a magnet. Additionally this filter can catalytically breakdown other impurities very similar to the way a catalytic converter works in your automobile. These processes ensure that you are getting the cleanest and best tasting water possible.

This economical filter will provide you with fresh and clean tasting water and ice cubes.

FITS IN PLACE OF:

- Amana* WF30, WF40, WF401, 12527301, 12527302, 12527303, 12527305, 12527307, 12527309, 12527504, 12388401, 12388402, 12388403, 12388406, 12388407, 12319801, 67003634
- Sears/Kenmore* 46-9014, 469014, 9014, 9014P, 04609904000
 Guaranteed by WaterSentinel*

FILTER FEATURES:

- Economical alternative to expensive substitutes
- · Delivers clean, clear water that looks and tastes great
- Will remove or reduce Chlorine, Tastes and Odors that may be present in your drinking water
- Designed to provide up to six months of life or 300 gallons
- Does not remove minerals which may be beneficial to health

Flow Rate:	.5 gpm/1.9 lpm
Operating Temperature:	33 - 100°F (0.6°C - 38°C)
Min Operating Pressure:	30 psi - (207 kPa)
Max Operating Pressure:	100 psi - (689 kPa)
Life:	6 months or 300 gallons (1,136 liters)

*AMANA CLEAN 'N CLEAR IS A REGISTERED TRADEMARK OF AMANA CORPORATION. KENMORE IS A REGISTERED TRADEMARK OF KCO LP, LLC.