



# SMF CoffeeTea Pro-2



**System Part #:** 80-6202TP  
**Replacement Cartridge #:** 108-067K-2

## Materials of Construction

Filter Media	Ion Exchange Resin
Housing	polypropylene
Head	Proprietary reinforced nylon

### Applications:

- Coffee tea and Espresso Machines
- Protection of Hot Beverage Equipment

### Benefits:

- No pre filter required
- Dirt, Chemical and Chloramines reduction
- Low pressure drop

### Features:

- High Efficiency Resin & Ultra High Porosity Carbon
- Nylon construction withstands high pressure
- Modular filter design for up to 80% less installation time!
- 40 times more dirt holding capacity than conventional carbon block filters and other polypropylene sediment filters!
- 30 times the chloramine reduction of a conventional carbon block
- 1<sup>st</sup> Jumbo Sanitary Filter on market
- Blending of treated and incoming water is optional!

### Specified to:

- Reduce scale build up
- Reduce Maintenance for coffee, tea & espresso machines
- Reduce tea turbidity to less than 65 NTU
- Reduce pitting and corrosion of equipment
- Reduce sediment, chlorine, chloramine and alkalinity

SMF CoffeeTea Pro-2 hardware has been independently tested against NSF/ANSI Std. 42  
 Do not use with water that is microbiologically unsafe or of unknown quality

## Cartridge Specifications and Performance Data

Model	Maximum Dimensions	Micron Rating	Initial ΔP (psi) at Flow Rate (gpm)	Scale Reduction at Flow rate (gpm)	Temperature Rating
<b>SMF CoffeeTea Pro - 2</b>	22" x 9" x 29"	5.0	1-5 psi @ 2 gpm @ 60 psi	3,000 gallons @ 2 gpm 11,400 liters @ 7.57 Lpm	40°F to 100°F

3980 Lakefield Court • Suwanee, GA 30024 USA

P: 678-475-0799 • 800-635-4017

F: 678-475-9126 • 800-811-7682

[www.selectoinc.com](http://www.selectoinc.com)

Ver. I, Aug 2010 JN