

3200



The Power RV 3200-
Your new favorite automatic
demand RV water pump.



Typical Applications

Water Treatment/RO
Agricultural Spraying
General Industrial
Automotive
RV and Coach water pumps

An incredible feature list, high quality components, plus amazing performance make the Remco 3200 a Power RV leader. The three-chamber high volume design, driven by a heavy-duty motor produces flow rates of 3GPM, making it the price to performance leader.



Positive displacement pump



Low amp draw easy connect fittings



Can run dry



Industry standard mount pattern



Quiet operation



Built in check valve



Demand pump



Thermally protected

PUMP

Type

Heavy 3 chamber positive displacement diaphragm pump, self priming, capable of being run dry

Mode

Demand

Liquid Temperature

140 degrees F

Priming Capabilities

up to 6 ft

Max Pressure

45 PSI (3.1 bar)

Inlet/Outlet Ports

1/2 NPT Male

Weight

2.5 lbs (1.14 kg)

MOTOR

Leads

18 AWG, 4.5" long with 2-pin connector

Duty Cycle

Intermittent

STANDARD PUMP CONFIGURATIONS

Model	Volt(V)	Switch	GPM/LPM	PSI/BAR	Max Draw (A)	Valves	Diaphragm	Ports	Lead Wire	Molded Connector
3264-1C1-15A	12V	Demand	3.0/11.6	45/3.1	5	Viton	Santoprene	1/2 MNPT	—	2-Pin
3264-1C1-25A	24V	Demand	3.0/11.6	45/3.1	2.5	Viton	Santoprene	1/2 MNPT	—	2-Pin

PUMP PERFORMANCE

PSI	Bar	GPM	LPM	Amps
OPEN	0.20	3.00	11.58	4.3
10	0.70	2.81	10.85	4.7
20	1.40	2.42	9.34	6.2
30	2.10	2.09	8.06	7.1
40	2.80	1.61	6.21	8.3
45	3.06	off	off	0



FITTINGS

Item Number	Size	Fitting Type	Material
QTE-332-12	1/2 MNPT x 1/2	HSE Barb Elbow Fitting	Nylon
QTS-332-12	1/2 MNPT x 1/2	HSE Barb Straight Fitting	Nylon



FILTER

Item Number	Inlet	Outlet	Mesh Size
10546	1/2" MNPT	1/2" FMPT Inline Filter/Strainer	50

Fittings and filter included with pump.



QTS-332-12 Fitting



QTE-332-12 Fitting



10546 Filter

