



Product Specifications



IN-STORE PRESENTATION



IN-HOME INSTALLATION



IN-HOME INSTALLATION WITH OPTIONAL HI-LO ARM



REDUCES:

- Chlorine
 - Sulfur Odor
 - Scale
- PLUS-> BACTERIOSTATIC*

FEATURES:

- Reduces aesthetic chlorine & Scale for softer cleaner skin and hair
- Chrome finish
- Easy to install – no tools required
- Cartridge change reminder sticker
- 5-year limited warranty

SINCE 1936



TESTED AND CERTIFIED BY NSF INTERNATIONAL

Level 2 Extra FILTRATION

RAINDISC® SHOWER HEAD FILTER

CARTRIDGE LIFE
6 MONTHS 10,000 GALLONS

MODEL
RDSH-C115

Model RDSH-C115

A smart addition to your water filtration set or the ideal product to provide differentiation in your showerhead assortment. Capitalize on two growth trends: consumer concerns over water quality and consumer preferences for performance showerheads. The Culligan® filtered showerhead delivers better water for a better shower!

Certified by NSF International, the patented filter media in this product reduces chlorine for a full 10,000 gallons. The cartridge also reduces sulfur odor and scale. Easy to install with no tools required, this unit will retro-fit to any existing ½-inch threaded shower arm. Put the strength of the consumer-trusted Culligan® brand to work for you with the value-added Culligan® filtered showerhead.

Package Includes:

- (1) RDSH-C115
- (1) WHR-140 shower filter
- Teflon® Tape
- Cartridge change reminder sticker
- Installation instructions
- Filter change instructions

Tools Required:

- None

Accessories:

- REA-150 RainDisc Shower Hi-Lo Arm (optional)

System Requirements:

- Water pressure of 40-100 psi (9.5 Lpm)
 - Water temperature of 40-120° F (4.4-49° C)
- Maximum flow rate of 2.5 gallons per minute as required by ASME Standards



Contact information:

Customer Service:

M-F 8:00 a.m. – 4:30 p.m. CST
Phone: 1-800-721-7360
Fax: 1-800-721-7390
International Phone: 1-920-457-2726
International Fax: 1-920-457-7366

Sales & Marketing Correspondence

P.O. Box 1086
Sheboygan, WI 53082-1086
Phone: 1-877-864-1484
Fax: 1-920-457-7366
Email: sales-marketing@culligan.com

Culligan International
Rosemont, Illinois 60018
www.culligan.com

WARNING: do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

- This device must be maintained according to manufacturer instructions including replacement of filter cartridges.
- Read all precautions on box and in manual before installing and using this system.



System Tested and Certified by NSF International against NSF / ANSI Standard 177 for the reduction of free available chlorine.

Individual Unit & Case

MODEL #	LEVEL	UNIT WT	UNIT DIMS H" x W" x D"	CASE QTY	CASE WT (LBS)	CASE DIMS L" x W" x D"	CASE CU FT	CASE UPC
RDSH-C115	Level 2	1.41	12 x 8.0 x 5.5	2	3.1	13.4" x 8.7" x 11.8"	.80	1 00 33663 00630 7

Replacement Parts & Accessories

MODEL #	LEVEL	UNIT WT	UNIT DIMS H" x W" x D"	CASE QTY	CASE WT (LBS)	CASE DIMS L" x W" x D"	CASE CU FT	CASE UPC
WHR-140	Level 2	0.53	5.5 x 2.75 x 2.75	6	3.4	10.5 x 5.75 x 6.0	.21	1 00 33663 00620 0
RDA-150	-	0.77	4.25 x 1.75 x 14.0	4	3.7	14.2 x 4.2 x 4.3	.15	1 00 33663 00674 1