

Aqua Flo Platinum QCRO Drinking Water System

Customized Drinking Water

Water conditions can vary even in the same community. The Aqua Flo Platinum QCRO System can be configured to meet your specific requirements. There are ten (10) interchangeable filters with a variety of treatment options that can be tailored to local water conditions, so your water is the best it can be.

The innovative Quick Change twist and lock design makes service simple. Twist off the old cartridge and twist on the new. No messy sump removal. High performance systems make drinking water better and life easier.

C IAPMO ®

QCRO4V-50 system certified by IAPMO R&T to NSF/ANSI 58 and CSA B483.1 for the reduction of the following substances, as verified and substantiated by test data: Barium, Cadmium, Copper, Fluoride, Hexavalent Chromium, Lead, Arsenic (V) (less than 300 ppb reduction), Radium 226/228, Selenium, TDS, Trivalent



IAPMO R&T certified for the reduction of PFOA/PFOS, lead and other harmful contaminants.



Product Specifications

Sediment Filters. Screens out sediments and particles. Various micron size filters are available.

Carbon Filters. Reduces elements that cause water to taste and smell unpleasant, including chlorine taste and odor.

Reverse Osmosis Filters. Reduces dissolved substances. Various capacity membranes are available.

Specialty Filters. Optimize drinking water taste and adjust to local water supply with a wide array of custom filter options.



Manifold Assembly. The single manifold ensures reliability. Houses four (4) separate filter technologies in a unique space saving design.

Shutoff Valve. Opens and closes the water supply to and from the reservoir

Reservoir Tank. Durable, high quality, powder coated, steel tank ensures you'll have a plentiful supply of refreshing water. Various size tanks are available.

Designer Faucet. Multiple styles and colors are available. (VS888 faucet shown)

Filter Cartridge and Single Stage Standalone System Specifications

	Sediment Filter	Carbon Block Filter	Carbon Block Filter	GAC Carbon Filter	pH Booster Filter Cartridge	Carbon Block - 1 Mic Filter
Purpose	Sediment Removal	Chlorine Taste and Odor	Chlorine Taste and Odor	Polishing - Taste and Odor	Raise pH of water and removal of chlorine, taste and odor	Chlorine Taste and Odor, Particulate Reduction
Туре	Polypropylene	Carbon Block	Carbon Block	Granular Activated Carbon Filter	pH Booster and Remineralizer	Carbon Block
Micron	5	5	50	_	-	1
Capacity*	2000 gallons	2000 gallons	2000 gallons	2000 gallons	To be changed every 6 months	750 Gallons
Minimum Flow Rate @ 60psi	0.5 gal/min	0.5 gal/min	0.5 gal/min	0.5 gal/min	0.5 gal/min	0.5 gal/min
Single Stage System Model #**	SEDQC1/4	CBQC1/4	CB50QC1/4	GACQC1/4	PHQC1/4	CB1QC1/4

May vary depending on water quality

RO Membrane

Feed Water Guidelines				
Maximum TDS	2000 ppm			
Hardness	<7gpg			
Iron (Fe)	<0.2ppm			
Manganese (Mn)	<0.05ppm			
Hydrogen Sulfide	0.0ppm			
Turbidity	<1.0NTU			
Feed Water Pressure	40-100psi			
Temperature	40-100°F			
pH Range	3.0-11.0			
Note: Pretreatment suggested if conditions exceed				

parameters. Must be installed on potable water.

Purpose	TDS Reduction
Туре	Thin film Composite Membrane
Recovery	25%
TDS Reduction %	95%
Rating	50 and 75 GPD
Minimum Flow Rate @ 60psi	0.5 gal/min
Quick Change Filter Dimensions	7.54 x 30.9 (2.96" x 12.17")
Inlet/Outlet Connections	1/4" Quick Connect
Working Temperature Range	4-38° C (40-100° F)
Working Pressure Range	207-828 kPa (30-120 psi)



QCRO4V-50 system certified by IAPMO R&T to NSF/ANSI 58 and CSA B483.1 for the reduction of the following substances, as verified and substantiated by test data: Barium, Cadmium, Copper, Fluoride, Hexavalent Chromium, Lead, Arsenic (V) (less than 300 ppb reduction), Radium 226/228, Selenium, TDS, Trivalent Chromium, Turbidity, and PFOA/PFOS.

Your Local Water Specialist



A Division of Canature



^{**} Single Stage Standalone System Port Connection Size - 1/4" Quick Connect