

K-NPDWS

Quick Change Drinking Water System

neo·PURE™



*Residential / Commercial
Filtration Applications*

Standard Features

- Manufactured in USA (filter and head)
- NP-QCB01PB 1 micron filter for sediment, chlorine taste and odor, cysts, and lead
- Self-contained sealed cartridge reduces potential for introducing bacteria
- NP-QCB01PB cartridge is tested and certified to NSF Standard 42 and 53
- Kit includes: single filter mounting bracket with mounting screws, inline valve assembly with quick-connect fittings, NP-QCB01PB filter, 6 feet of 1/4" tubing, lead-free angle stop adapter

Also available with drinking water faucet FCT-502-CH (chrome) or FCT-502-BN (brushed nickel)

Applications:

- Drinking Water Systems



Tested and certified to NSF Standard 42 and 53. Only applies to NP-QCB01PB filter cartridge. Does not apply to K-NPQ1 system.

Specifications

Filter Media

Coconut shell carbon block with phosphate

Filter Capacity

1250 gallons for lead

Micron Rating (Nominal)

1 micron

Flow Rate

0.5 gpm

Connection Type

1/4" quick connect

Operating Temperature

35-100°F

Operating Pressure (Maximum)

125 psi

Height, Width, Depth

13.5"H x 3.25"W x 3.5"D

WARNING:

Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

NeoLogic
SOLUTIONS
Filtration Division

9450 SW Gemini Dr, ECM #83358, Beaverton, OR 97008
Tel 855-896-3525 | Fax 866-409-9622
www.neologicsolutions.com
email: info@neologicsolutions.com
STUART, FL | BEAVERTON, OR | GREENVILLE, SC | SAN DIEGO, CA

Questions?

Ask one of our
Service Representatives:
Mon-Fri 8a-8p, Sat 8:30a-4:30p EST

We ship 6 days
a week! **FedEx**