RO Storage POPUPE Tanks




neoPure[™] Reverse Osmosis Tanks are built with FDA approved materials. The water storage chamber features a virgin polypropylene liner, high-grade chlorobutyl diaphragm and stainless steel water connection. The diaphragm is post cured to ensure that your water is tasteless, odorless and contaminant free. The tank is built with a sealed brass air valve and o-ring sealed cap to ensure a leak-free air chamber.

Features:

- · Stainless steel water connection
- · Post Cured Butyl Disphragm
- · Virgin polypropylene liner
- [.] Two part epoxy primer, polyurethane paint finish
- [.] Plastic tank stand included
- · NSF-58 and CE approved
- Compatible with PAE & Amtrol equivalent Reverse Osmosis Tanks

PRODUCT SPECIFICATIONS

Tested and Certified



RO Storage ROPUCe Tanks

PRODUCT

Part Number	Color	Total Volume Gallons*	Precharge	Approximate Holding Capacity at 40 psi**	Male Plumbing Connection
ROT-1.0-14W	White	1	6 psi	.5 gal / 2L	1/4"MPT
ROT-3.2W	White	3.2	6 psi	2 gal / 7.6L	1/4"MPT
ROT-3.2E	Black	3.2	6 psi	2 gal / 7.6L	1/4"MPT
ROT-4.5W	White	4.5	6 psi	3 gal / 11.4L	1/4"MPT
ROT-4.5E	Black	4.5	6 psi	3 gal / 11.4L	1/4"MPT
ROT-11-34W	White	11	10 psi	7 gal /26.5L	3/4"MPT
ROT-20-34W	White	20	10 psi	9.25 gal / 35.01L	3/4"MPT
ROT-40-10W	White	40	28 psi	22.5 gal / 85.17L	1"MPT

*Volume above is total capacity, not water storage volume.

**Higher precharge pressures will lower holding capacities.

DIMENSIONS

	A (diameter)	B (height)	BASE
ROT-1.0-14W ROT-3.2W ROT-3.2E ROT-4.5W ROT-4.5E ROT-11-34W ROT-20-34W	5.9" 9.5" 9.6" 9.6" 15.1" 15.2"	8.7" 13.8" 13.8" 15.15" 15.15" 20.1" 27.5"	na na na na 5.8″ 5.8″
ROT-40-10W	17.7″	35.2″	na

