

# eXact® LEADQuick™

The new eXact® LEADQuick™ Advanced Photometer from Industrial Test Systems, Inc. (ITS) is the perfect meter for all your water quality testing needs. No visual color matching required means the eXact® LEADQuick™ takes the guesswork out of water testing.

- **Direct read parameters:** Lead in Paint, Lead in Water, Lead in Soil, Mercury in Water, and Cadmium in Water.
- **Easy-to-use eXact® Strip/Photometer reagent delivery system** (US Patent #7,333,194) delivers reagents safely without the need to count drops or crush tablets
- **0.01 ppm (mg/L) precision** with no visual color matching required
- **Waterproof meter (IP-67) and it floats**
- **2-Year warranty with satisfaction guarantee**
- **Automatic test timer & 120 test memory** (saves last 20 tests per menu)
- **Autocalibrated meter**
- **No-slip grip housing and simple 3-button control**
- **Lightweight** (weighs only 6 oz with batteries installed)
- **Environmentally friendly** (recyclable parts and uses 60% less reagents than 10mL sample tests)
- **Private labeling and menu customization available**

**WATERPROOF  
(IP-67)**



## TECHNICAL SPECIFICATIONS:

<b>Measurement Method:</b>	Photometric Light Source: Light Emitting Diode (LED)
<b>Wavelength:</b>	476 nm
<b>Memory:</b>	20 tests per menu; 120 total
<b>Programmed Tests:</b>	Lead in Paint, Lead in Water, Lead in Soil, Mercury in Water, and Cadmium in Water
<b>Photometric Precision:</b>	.001
<b>Display:</b>	3-digit customized liquid crystal display with annunciators
<b>Cell Pathlength:</b>	20mm
<b>Cell Chamber:</b>	Custom-molded, proprietary, PET plastic fused into chamber, non-removable
<b>Sample Required:</b>	4 mL (0.13 oz)
<b>Reagent System:</b>	Utilizes patented eXact® Strip Micro reagent delivery system
<b>Operating Temperature Range:</b>	0 - 50°C (32° - 122°F)
<b>Power Supply:</b>	(4) AAA alkaline batteries
<b>Battery Life:</b>	>2000 tests with alkaline batteries
<b>Electromagnetic Compliance (EMC):</b>	Emitted Interference - EN 61326; Immunity to Interference - EN 61326
<b>Waterproof Rating:</b>	Exceeds IP67
<b>Instrument Weight:</b>	140 g (5 oz)
<b>Instrument Dimensions:</b>	5 (W) x 3.5 (D) x 16.5 (H) cm; (2 x 1.4 x 6.375 in)
<b>Government Compliance:</b>	European CE Mark

For more information about this and our complete line of test strips, reagent and water quality testing devices, please call or email as listed below.



**Industrial Test Systems, Inc.**  
1875 Langston Street  
Rock Hill, SC 29730  
800.861.9712  
803. 329.9712  
its@sensafe.com  
www.sensafe.com/

**ITS Europe, Ltd.**  
The UK Centre for Homeland Security  
Building 7, Chilmark  
Salisbury, Wiltshire SP3 5DU UK  
Phone: +44 1722 717911  
Fax: +44 1722 717941  
sales@sensafe.com

**www.SENSAFE.com**