SCIENTIFIC

SMF IC614-2

Fountain Machine Application

- Improves taste and reduces odor
- Low pressure drop
- Sanitary quick replacement



System Part No. 80-6142 Replacement Cartridge No. 108-0142

Cartridge Specification & Performance Data:

Flow rate	14 gpm
Maximum Dimensions	22" x 9" x 23"
Shipping Weight	27 lbs
Micron Rating	0.5
Initial ΔP , Flow rate	5 psi , 7gpm at 60 psi
Chloramine reduction, Flow rate	30,000 gal, 7.4 gpm
Chlorine reduction, Flow rate	150,000 gal, 14 gpm
Temperature Rating	40°F - 100°F

Materials of construction:

Filter Media	Hollow Carbon
Housing	Polypropylene
Head	Proprietary reinforced nylon

(NSF.)

SMF IC614 has been tested and certified by NSF International against NSF/ANSI Std. 42 & Std. 53. Do not use with water that is microbiologically unsafe or of unknown quality

Selecto Scientific Inc. 3980 Lakefield Court, Suwanee, GA 30024 USA Phone: 678 475 0799 | 800 635 4017 Fax: 678 475 9126 | 800 811 7682 www.selectoinc.com Email: Customer-Service@ SelectoInc.com