
G John Guest[®]

The Lead-Free Push-Fit Solution



- Easy to Use
- Can be Used with Copper, CPVC or PEX Pipe
- No Tools Required
- Installation Time Reduced by 40%
- JG Twist & Lock for Added Security
- Suitable for Hot and Cold Water Applications

-

stant

- Leak-Proof Seal
- Lead Free
- UV Resistant

Applications:

- Water Filtration/Softener Installs
- Plumbing Repair and Remodel
- Marine and R.V.

1.800.945.4872 info@jgusa.com www.johnguest.com



The Black PEI Range of Twist & Lock Fittings is offered in 3/4" and 1" CTS sizes. They have specifically for designed Water been Filtration/Softener Installs; however, they are also suitable for applications in Plumbing Repair and Remodel, Marine and R.V. The fittings are manufactured from high quality engineered plastic with EPDM O-rings. Speedfit Push-in system is suitable for hot and cold water plumbing applications.

CC	UPL	ED
CC	UPL	

PART NO.	SIZE CTS
PEI0428E PEI0436E	3/4″ 1″

ELBOW

PART NO.	SIZE CTS
PEI0328E PEI0336E	3/4" 1"

TEE

PART NO.	SIZE CTS
PEI0228E PEI0236E	3/4" 1"

Working Pressures and Temperatures: Application: Water

Max. Pressure	Max Temperature
160 psi	73°F
100 psi	190°F
80 psi	200°F

PA

PS

PS

MALE CONNECTOR

6	~			
Y.	-	-	-	

RT NO.	SIZE CTS x NPT
El012826E	3/4″ x 3/4″
El013628E	1″ x 1″

MALE STEM ADAPTER

PART NO.	SIZE CTS x NPT
PSEI052826E PSEI053628E	3/4″ x 3/4″ 1″ x 1″

STEM ELBOW



PART NO.	SIZE CTS x STEM
	/4" x 1 1/4"

*Available through Clack Corporation

STEM CONNECTOR

Sec. 1	PART NO.	SIZE
		CTS x STEM
_	*NC2438E	1″ x 1 1/4″

*Available through Clack Corporation







🕂 John Guest 1.800.945.4872 info@jgusa.com www.johnguest.com