

SMF IC620-2

System Part No. 80-6202
Replacement Cartridge No. 108-0202

Fountain Machine Application

- Improves taste and reduces odor
- Low pressure drop
- Sanitary quick replacement



Cartridge Specification & Performance Data:

| | |
|---------------------------------------|--------------------------|
| Flow rate | 15 gpm |
| Maximum Dimensions | 22" x 9" x 29" |
| Micron Rating | 0.5 |
| Initial ΔP (psi), Flow rate (gpm) | 5 psi , 15 gpm at 60 psi |
| Chloramine reduction, Flow Rate (gpm) | 60,000 gal, 5 gpm* |
| | 45,000 gal, 6 gpm |
| | 40,000 gal, 8 gpm |
| Chlorine Reduction, Flow Rate (gpm) | 200,000 gal, 15 gpm |
| Temperature Rating | 40°F - 100°F |

Materials of construction:

| | |
|--------------|------------------------------|
| Filter Media | Hollow Carbon |
| Housing | Polypropylene |
| Head | Proprietary reinforced nylon |

* Independently tested against NSF 42 by pace labs



SMF IC620-2 has been tested and certified by NSF International against NSF/ANSI Std. 42 & Std. 53. Do not use with water that is microbiologically unsafe or of unknown quality