

# GE® Reverse Osmosis Twist and Lock Filtration System Replacement Membrane



Model# FQROMF



## FEATURES

Arsenic Reduction	98%
Asbestos Reduction	99.9%
Chlorine Taste and Odor Reduction	96.1%
Chromium III Reduction	96.5%
Chromium VI Reduction	97.5%
Copper Reduction	97.5%
Cysts Reduction	99.99%
Lead Reduction	97.6%
Sodium Reduction	91.6%
TDS Reduction	91.6%
Turbidity Reduction	99.9%
Feed Water pH Limits	4-10
Feed Water Pressure (psi)	40 Min - 125 Max.
Feed Water Temperature	40-100 F
Filter Cartridge	Carbon Block
Filter Change Indicator	LED
Fittings	1/4" - Push to Connect
Max. Filtered Water Flow (gpm)	0.75
NSF Particulate Reduction	Class III
Plumbing Connections	1/4" Inlet - 3/8" Outlet
Style	Twist and Lock

- Membrane fits PXRQ15F, PNRQ15F, PNRQ20F, PNRQ20R and PNRQ21R reverse osmosis systems
- Twist and Lock design allows you to remove and install filters in seconds. A simple quarter-turn twist and you're done

Have more questions? Please contact 1-800-626-2005

# GE® Reverse Osmosis Twist and Lock Filtration System Replacement Membrane



Model# FQROMF

## APPROXIMATE DIMENSIONS (HxDxW)

- x x

## WARRANTY

- Warranty Notes - See written warranty for full details

Have more questions? Please contact 1-800-626-2005