

FloPlus® WFP3/4A series

s y s t e m s

A TASTEFUL ADDITION TO ANY HOME

FloPlus® whole house high-flow chlorine and cyst reduction systems

American Plumber® introduces the WFP3/4A series of standard high-flow carbon block systems. Utilizing our patented Fibredyne® carbon technology, these systems offer extremely low pressure drop and maintain a 0.5-micron efficiency for the best chlorine taste & odor reduction and the reduction of cysts.



features

- ★ Nominal 0.5-micron filtration rating
- ★ Maximum chlorine taste & odor reduction and excellent dirt-holding capacity
- ★ Radial flow filtration for longer filter life
- ★ Available with clear or opaque housings

benefits

- ★ Removes 99.95% of *Cryptosporidium* and *Giardia* cysts
- ★ Low pressure drop and high flow
- ★ Long cartridge life for reduced maintenance
- ★ Clear housing allows visual inspection of the filter working

applications

- ★ Ideal for low water pressure situations
- ★ Whole house cyst and chlorine reduction
- ★ Well and city water installations
- ★ Applications requiring clean, safe water

American
PLUMBER®
Water Filtration Products

system specifications

	WFP3/4-10A	WFP3/4C-10A
rating (nominal)	0.5 micron	0.5 micron
max pressure	125 psi	125 psi
max temperature	125°F	125°F
inlet/outlet	3/4-inch	3/4-inch
cartridge size	2 7/8" x 9 3/4"	2 7/8" x 9 3/4"

system includes

	WFP3/4-10A	WFP3/4C-10A
sump	153085	153128
cap	154101	154101
o-ring	152030	152030
cartridge	555019-51	555019-51
bracket	152040	152040
wrench	152037	152037
manual	yes	yes

materials of construction

	WFP3/4-10A	WFP3/4C-10A
housing	polypropylene	polypropylene
cap	reinforced polypropylene	reinforced polypropylene
o-ring	buna-n	buna-n

system dimensions

	WFP3/4-10A	WFP3/4C-10A
height	12 1/4"	12 1/4"
diameter	5 1/8"	5 1/8"

replacement cartridges

model	description	part number
WFP-10A	10-inch cartridge	555019-51

See WFP Series Product Profile (300062) for cartridge specifications.

systems

model	description	part number
WFP3/4-10A	high flow chlorine & cyst	152089
WFP3/4C-10A	high flow chlorine & cyst	152090



WARNING: Do not use with water that is microbiologically unsafe, or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used on disinfected waters that may contain filterable cysts.

CAUTION: Filter must be protected against freezing, which may cause cracking of the filter and water leakage.

NOTE: Contaminants or other substances removed or reduced by this water treatment device are not necessarily in your water.

American
PLUMBER®

5730 North Glen Park Road
Milwaukee, WI 53209 USA
Phone 800.645.5428 • Fax 888.588.9388
www.americanplumber.com