


CHEMICAL RESISTANCE GUIDE

STENNER PUMPS

Ratings Key – Chemical Effect

- A** Fluid has minor or no effects
- B** Fluid has minor to moderate effects
- C** Fluid has severe effects
- * No data available

 **CAUTION** The information is provided ONLY as a guide to assist in determining chemical compatibility for wetted components. Testing under the specific conditions of the application is recommended. Stenner Pump Company assumes no responsibility for its accuracy. Outside factors including but not limited to temperature, pressure, mechanical stress, and solution concentration can affect material compatibility in a particular application. Stenner makes no warranty, expressed or implied, as to the accuracy of this guide or any materials' suitability for fitness or purpose for any application. User assumes all risk and liability for use of this guide.

Chemical / Solution	PP/Santoprene®	Versilon™	PVC	LDPE	FKM
Acetic Acid 20%	A	B	B	A	*
Acetic Acid 30%	B	C	C	A	B
Acetic Acid, Glacial	C	C	C	C	C
Acetic Anhydride	B	C	C	C	C
Aliphatic Hydrocarbons	B	B	B	B	*
Aluminum Chloride	A	A	A	B	A
Aluminum Sulfate	A	A	A	A	A
Alums	A	A	A	A	A
Ammonium Acetate	B	B	A	A	A
Ammonium Carbonate	A	A	A	A	A
Ammonium Chloride	A	B	A	B	A
Ammonium Hydroxide	A	B	A	A	B
Ammonium Nitrate	A	A	A	A	B
Ammonium Phosphate	A	A	A	A	A
Ammonium Sulfate	A	A	A	A	B
Amyl Acetate	A	C	C	C	C
Aniline	B	C	C	C	C
Antimony Salts	A	A	A	B	*
Arsenic Salts	A	A	A	B	*
Barium Hydroxide	A	A	A	B	A
Barium Salts	A	*	A	B	*
Beer	A	A	A	A	A
Benzene	C	C	C	C	B
Benzoic Acid	A	C	A	A	A
Bleach 5.25%	A	A	A	A	*
Boric Acid	A	A	A	A	A
Bromine	A	B	B	B	A
Butyl Acetate	A	C	C	C	C
Butyric Acid	A	C	B	C	*
Calcium Chloride	A	A	B	A	A
Calcium Hydroxide	A	C	A	A	A
Calcium Hypochlorite 5%	A	B	A	A	A
Calcium Salts	A	A	A	A	*
Carbon Disulfide	C	C	C	C	A
Carbon Tetrachloride	C	C	C	C	A

Chemical / Solution	PP/Santoprene®	Versilon™	PVC	LDPE	FKM
Castor Oil	B	A	A	*	A
Chlorine <i>see Sodium Hypochlorite</i>	*	*	*	*	*
Chloroacetic Acid	A	C	B	C	C
Chloroform	C	C	C	C	A
Chlorosulfonic Acid	B	C	C	C	C
Chromic Acid < 50%	B	C	B	A	A
Chromium Salts	A	*	A	B	*
Citric Acid	B	B	B	C	A
Copper Chloride	A	A	A	A	A
Copper Sulfate	A	A	A	A	A
Cottonseed Oil	B	A	B	A	A
Ethyl Acetate	A	C	C	C	C
Ethyl Alcohol	B	C	C	B	B
Ethyl Chloride	C	C	C	C	A
Ethylene Dichloride	C	C	C	C	A
Ethylene Glycol	A	A	A	A	A
Ethylene Oxide	B	A	C	C	C
Eucalyptus Oil	C	B	C	C	*
Fatty Acids	C	B	A	A	A
Ferric Chloride	A	A	A	A	A
Ferric Sulfate	A	A	A	A	A
Ferrous Chloride	A	A	A	A	A
Ferrous Sulfate	A	A	A	A	A
Fluoboric Acid	A	C	A	C	*
Fluosilicic Acid	A	A	A	A	A
Formaldehyde < 40%	A	B	A	C	C
Formic Acid	A	C	B	C	C
Glucose	A	A	A	A	A
Glue	A	A	A	A	A
Glycerin	A	A	A	A	A
Hydrochloric Acid 20%	A	C	A	A	A
Hydrochloric Acid 37%	A	C	A	A	A
Hydrocyanic Acid	A	B	A	A	A
Hydrofluoric Acid < 48%	A	C	B	A	A

Chemical / Solution	PP/Santoprene®	Versilon™	PVC	LDPE	FKM
Hydrofluoric Acid 48-75%	A	C	C	C	A
Hydrofluoric Acid, anhydrous	B	C	C	C	C
Hydrogen Peroxide < 50%	A	B	A	B	A
Hydrogen Sulfide	A	A	B	A	C
Iodine	A	A	C	B	A
Lactic Acid	A	B	B	A	A
Lead Acetate	B	A	A	A	C
Linseed Oil	B	A	A	A	A
Limonene	C	B	B	B	*
Lubricating Oils	C	A	B	C	A
Magnesium Chloride	A	A	B	A	A
Magnesium Hydroxide	A	A	A	A	A
Magnesium Sulfate	A	A	A	A	A
Malic Acid	A	B	A	A	A
Manganese Salts	A	A	A	A	*
Mercuric Chloride	A	A	A	A	A
Methylene Chloride	C	C	C	C	B
Mineral Oil	B	A	B	B	A
Mineral Spirits	C	A	B	B	A
Muriatic Acid, 20° Baume	A	C	A	A	A
Nitric Acid < 10%	A	C	A	B	A
Nitric Acid 10-30%	B	C	A	C	A
Nitric Acid 30-60%	C	C	B	C	A
Nitric Acid 70%	C	C	B	C	A
Nitric Acid, red fuming	C	C	C	C	C
Nitrous Acid	A	B	*	*	B
Oleic Acid	A	B	C	C	B
Oleum 20-25%	C	C	C	C	*
Oxalic Acid	A	C	B	A	A
Palmitic Acid	A	B	B	A	A
Petroleum Distillates	C	B	B	C	*
Phenol	B	C	C	B	A
Phosphoric Acid	A	C	A	A	A
Phthalic Acid	A	C	A	A	A
Pickling Solutions	A	C	*	*	B
Plating Solutions	A	C	*	*	A
Polyphosphate	A	A	A	A	*
Potassium Carbonate	A	A	A	A	A
Potassium Chlorate	A	A	A	A	A
Potassium Hydroxide	A	A	A	A	C
Potassium Dichromate	A	A	A	A	A
Potassium Iodide	A	A	B	B	A

Chemical / Solution	PP/Santoprene®	Versilon™	PVC	LDPE	FKM
Potassium Permanganate	A	A	A	A	A
Sea Water	A	A	A	A	A
Silicone Oil	C	A	A	B	A
Silver Nitrate	A	A	A	A	A
Soap Solutions	A	A	A	C	A
Sodium	A	A	A	A	*
Sodium Bisulfate	A	A	A	A	A
Sodium Bisulfite	A	A	A	A	A
Sodium Borate	A	A	A	A	A
Sodium Carbonate	A	A	A	A	A
Sodium Chlorate	A	A	A	A	A
Sodium Chloride	A	A	A	A	A
Sodium Dichromate 20%	A	*	B	*	A
Sodium Hydroxide < 20%	A	B	A	B	A
Sodium Hydroxide 20-46.5%	A	C	A	B	A
Sodium Hypochlorite 5%	A†	B	A	A	A
Sodium Hypochlorite 6-15%	A†	B	A	A	*
Sodium Nitrate	A	A	A	A	A
Sodium Silicate	A	A	A	A	A
Sodium Sulfide	A	A	A	A	A
Sodium Sulfite	A	A	A	A	A
Solvents	C	B	B	B	*
Soybean Oil	B	A	A	A	A
Stannous Chloride 15%	A	A	A	B	A
Stearic Acid	A	B	B	B	A
Sulfur Dioxide liquid	A	C	C	C	B
Sulfur Trioxide	B	C	A	C	A
Sulfuric Acid < 40%	B	B	B	B	A
Sulfuric Acid > 40%	C	C	C	C	A
Sulfurous Acid	A	A	A	B	C
Tannic Acid 10%	A	B	A	B	A
Tanning Liquors	A	A	A	A	A
Tartaric Acid	A	A	A	A	A
Titanium Salts	A	A	A	B	*
Triethanolamine	A	C	C	C	C
Tri Sodium Phosphate	A	A	A	A	A
Tung Oil	B	B	C	C	A
Turpentine	B	B	C	C	A
Urea	B	A	B	A	A
Water & Brine	A	A	A	A	A
Zinc Chloride	A	A	B	A	A
Zinc Salts	A	A	A	A	*

† Products tested and certified by WQA to NSF/ANSI Standard 61 for contact with Sodium Hypochlorite and Water only and Standard NSF/ANSI 372 for low lead compliance.
NOTE: FKM tested to NSF/ANSI 61 with water only.

This information is not intended for specific application purposes. Stenner Pump Company reserves the right to make changes to prices, products, and specifications at any time without prior notice.

FCRG0415



STENNER PUMP COMPANY

Jacksonville, Florida USA

www.stenner.com

© Stenner Pump Company All Rights Reserved