

**SIDE MOUNT BRACKET**

| Part No. | Description            |
|----------|------------------------|
| 10605-00 | 90° Side Mount Bracket |

10605-00



**SPARE PARTS FOR 500-1000 GPH**

| Part No. | Description                               |
|----------|---|
| 92105    | DuraPort Straight, assembled port fitting |
| 92205    | DuraPort 90°, assembled port fitting      |
| 51123PK  | Flow Rite, Straight, Quick Connect, male  |
| 51124PK  | Flow Rite, 90°, Quick Connect, male       |

**SPARE PARTS FOR 1250, 1600, 2200 GPH**

| Part No.   | Description                              |
|------------|--|
| 10606-00   | 1 1/8" Threaded Discharge Port 1600/2200 |
| 10607-00   | 1 1/4" Threaded Discharge Port 1600/2200 |
| 54061-24PK | 1" Threaded Discharge Port 1600/2200     |

**CHECK VALVES FOR 600-1250 GPH**

Check Valve Flapper and Check Valve Washer available on request.

**CARTRIDGE MOTOR - REPLACEMENT PUMP**

Upgrade the output of your bilge pump in a matter of a few minutes by replacing the cartridge. Cleaning debris from the impeller has never been simpler or easier.

| Part No. | Description                  |
|----------|------------------------------|
| 28552    | Cartridge Motor 500 GPH 12V  |
| 28572    | Cartridge Motor 750 GPH 12V  |
| 28512    | Cartridge Motor 1000 GPH 12V |
| JP-42522 | Cartridge Motor 1250 GPH 12V |



**STRAINER/ VALVE/ Y-CONNECTION**

**IN-LINE NON-RETURN VALVE**

| Part No. | Description              | Connection               |
|----------|--------------------------|--------------------------|
| 09-24792 | In-Line Non-Return Valve | 25/38 mm (1" / 1 1/2")   |
| 09-24818 | In-Line Non-Return Valve | 19/32 mm (3/4" / 1 1/4") |

- Designed to install in-line
- Maintains prime in a suction or discharge line
- Easy to maintain and clean without any tools
- Designed to prevent bilge debris blocking the inlet suction line
- Reduce the risk of debris entering and blocking the pump
- Maintain prime in the suction line
- Easy to maintain and clean without any tools



**BILGE STRAINER WITH NON-RETURN VALVE**

| Part No. | Description | Connection                                       |
|----------|-------------|--|
| 09-24794 | Strainer    | 19/32 mm (3/4" / 1 1/4"), 25/38 mm (1" / 1 1/2") |

**Y-CONNECTION**

| Part No. | Description                 |
|----------|-----------------------------|
| 01-24814 | Y-connection 38X38X25       |
| 01-24815 | Y-connection 29/32X29/32X19 |

- Y-connections enable two pumps to discharge through a single line.
- Diverter valve is not required.

**Bilge Pump Systems - Manual and Electrical Bilge Pumps in Combination**

