

# Hypure\* PF

## Resin Bonded Filter Cartridge

The Hypure PF filter is a resin-bonded, spiral wound filter cartridge suitable for a wide range of applications. Hypure PF utilizes phenolic resin impregnated, long-strand polyester fibers for efficiency and long life. Uses for Hypure PF include adhesives, coatings, and inks, and many more applications both water and solvent based.

### Features and Benefits

- High dirt holding capacity
- Wide range of micron retention
- Faster flow rates
- High efficiency
- Less change-outs
- Consistent quality

### Applications

- Printing inks
- Water
- Hot, non-aqueous fluids
- Adhesives
- Antifreeze
- Insecticides
- Photo resists
- Solvents
- Paints and varnishes
- Thinners
- Fuels and Lubricating oils
- Coolants
- Coatings

### Available Nominal Micron Ratings

3, 5, 10, 15, 25, 50, 75, 100  $\mu\text{m}$



### Materials of Construction

Phenolic resin impregnated, wound polyester fibers with coreless construction.

### Dimensions

Outside Diameter – 2.5" (6.4 cm)

Inside Diameter – 1" (2.5 cm)

### Lengths

9  $\frac{3}{4}$ " (24.8 cm)      29  $\frac{1}{4}$ " (74.3 cm)

10" (25.4 cm)      30" (76.2 cm)

19  $\frac{1}{2}$ " (49.5 m)      39" (99.1 cm)

20" (50.8 cm)      40" (101 cm)



Find a contact near you by  
visiting [gewater.com](http://gewater.com) or  
e-mailing [custhelp@ge.com](mailto:custhelp@ge.com).

**Global Headquarters**  
Trevose, PA  
+1-215-355-3300

**Americas**  
Watertown, MA  
+1-617-926-2500

**Europe/Middle East/Africa**  
Heverlee, Belgium  
+32-16-40-20-00


**Asia/Pacific**  
Shanghai, China  
+86 (0) 411-8366-6489

©2007, General Electric Company. All rights reserved.

\*Trademark of General Electric Company; may be registered in one or more countries.

FS1641EN 0702

## Nomograph for High Viscosity Liquids Per 10 Inch Length



Note: SSU conversion assumes a gravity limit of 1.0

### Operational Limits

Maximum Temperature Rating      250°F (121°C) in gases,  
 180°F (82°C) in aqueous and non-aqueous liquids

### Non Aqueous Liquids

To size a housing, determine several variables: the desired micron size, the pressure drop permitted, the maximum flow rate and the fluid viscosity. If any three are known, the fourth may be plotted on the nomograph above. Example:

1. Draw a line from the desired Micron Size (Cartridge Type) through the desired initial Pressure Drop to intersect with Index Line.
2. Draw a second line from Fluid Viscosity through the Index Line intersection to determine the recommended Flow Rate
3. Read Flow Rate in GPM. Nomograph for High Viscosity Liquids Per 10 Inch Length

### Ordering Information

Type	Nominal Micron Rating (µm)	Length inch (cm)	End #1 Adapter	End #2 Adapter	Elastomer Material
HPF	03 = 3	9 ¾ (24.8)	E = 222 O-ring L = Extended Core X = Standard Plain End (no gasket)	S = Solid End X = Plain End (no gasket)	O-Rings S= Silicone V = Viton <sup>1</sup> B = Buna
	05 = 5	10 (25.4)			
	10 = 10	19½ (49.5)			
	15 = 15	20 (50.8)			
	25 = 25	29¼ (74.3)			
	50 = 50	30 (76.2)			
	75 = 75	39 (99.1)			
	100 = 100	40 (101.6)			
					<sup>1</sup> Viton is a registered trademark of Dupont

End adapters extended core option - polyester extended core 222 O-Ring