

NP-3M704

SQC Compatible Replacement Cartridges



Residential/Commercial Filtration Applications

STANDARD FEATURES

- Manufactured in South Korea
- Formally NP-SQC704
- Compatible with the Water Factory Systems SQC3 and SQC4 systems
- Replacement for 47-55704G2, 47-557047CM, and PSQC-3*
- Quick change design for easy installation
- NP-3M704 is Certified to NSF/ANSI 42 for material safety requirements only. Certified to NSF/ANSI/CAN 372 lead-free requirements only.

*Claims of compatibility not certified by IAPMO. Do not use with water that is microbiologically unsafe or of unknown quality, without adequate disinfection before or after the system.

PRODUCT SPECIFICATIONS



Flow Rate
0.6gpm or 1037.6 GPD



Change Frequency
24 - 36 months



Operating Temperature
34 to 100°F (4.4 to 37.8°C)*



Capacity
2500 Gallons



Operating Pressure
30 - 120 psi



Materials of Construction
Filter Media: Carbon Block

Tested and Certified



Certified to NSF/ANSI 42 for material safety requirements only.
Certified to NSF/ANSI/CAN 372 lead-free requirements only.

QUESTIONS?

Ask our Service Representatives at:
888.859.1188 Mon. - Fri. 8a - 8p, Sat 8:30a - 4:30p EST.

Neologic Inc. | Greenville SC | Salt Lake City UT | Houston TX

Note: Flush filter for 5 minutes.

*Temperature ratings vary and depend on pressure and time under load.

CONTAMINANTS REDUCED

- Chlorine Taste & Odor
- Sediment
- Dirt
- Rust