

Bio-Logic®

Pure Water Pack™



GERMICIDAL ULTRAVIOLET LAMP DATA

Lamp Number	Purifier Model No.	Lamp Watts ③	Ultraviolet Output		Effective Life (Hours)
			Total Watts ①	Microwatts at One Meter ②	
05-1366-R	BIO1.5 PWP	14	4	40	10,000

Bio-Logic® Pure Water Pack employs a low pressure germicidal ultraviolet lamp that affords maximum efficiency, low power requirements and long lamp life in producing the required germicidal rays.

- ① Maximum rated output at 254 nanometers at 100 hours and 80° F (Approx).
- ② Microwatts per square centimeter at one meter from lamp
- ③ Lamp watts only, does not include power supply loss.

CAUTION: Exposure to direct or reflected germicidal ultraviolet rays will cause painful eye irritation and reddening of the skin. Personnel subject to such exposure must wear suitable faceshield, gloves and protective clothing.

Hg - LAMP CONTAINS MERCURY, manage in accord with disposal laws, see: www.lamprecycle.org.

The information and recommendations contained in this publication are based upon data collected by the Atlantic Ultraviolet Corporation and are believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. Specifications and information are subject to change without notice.

