

# STREAMLABS™ SMARTHOME MONITOR

## SPECIFICATIONS SHEET



### DESCRIPTION

App-enabled Home Water Monitoring & Leak Detection System.

Applications:

- Water Usage Tracking
- Leak Detection
- Submetering
- Sustainability and Water Conservation



UMFT-1000

### SPECIFICATIONS

App Compatibility	iOS 11.0 or later, compatible with iPhone or iPad Android 6.0 or later, phone or tablet
Compatible Pipe Sizes	3/4", 1" Copper Tube Size (CTS)
Compatible Pipe Types	Copper Type M & L; PEX; CPVC
Universal Power Supply	Input: 100-240VAC~50/60Hz, 0.2A; Output: 5.9V @ 0.6A UL Listed (included)
Water Temperature	min. 40° F (4.4° C) / max. 80° F (26.6° C)
Operating Pressure	max. 232 psi (16 bar) Limited by Pipe
Ambient Temperature	min. 32° F (0° C) / max. 115° F (46.1° C)
Operating Environment	Indoor use only
Network	Wi-Fi 802.11b/g/n, 2.4 GHz

### LEAK DETECTION SETTINGS

SETTINGS	USER DEFINABLE
Slow Leak	0.25, 0.5, 1.0 GPM for 5, 10, 15, 20, 30, or 60 mins
Major Leak	2.0, 4.0, 6.0 GPM for 2.5, 5, 10, 15, 20, or 30 mins
Away Mode	0.25 for 15 seconds

*\*For Copper Type L, leak detection begins at greater than .5 GPM*

### LISTINGS AND APPROVALS

FCC/IC

