

# NP-3M704

## SQC Compatible Replacement Cartridges

**neo·PURE**<sup>®</sup>  
Filtration Products



Component NP-3M704 is tested and certified by WQA to NSF/ANSI 372 and NSF/ANSI 42 for material safety and structural integrity requirements



### Residential/Commercial Filtration Applications

## Standard Features

- Manufactured in South Korea
- Formally NP-SQC704
- Compatible with the Water Factory Systems SQC3 and SQC4 systems
- Replacement for 47-55704G2, 47-557047CM, and PSQC-3\*
- Reduces chlorine taste and odor, and sediment, dirt and rust
- Quick change design for easy installation
- NP-3M704 is tested and certified by WQA to NSF/ANSI 372 and NSF/ANSI 42 for material safety and structural integrity requirements

\*Not tested by WQA in these systems

## Product Specifications

### Micron Rating (Nominal)

5 microns

### Flow Rate

0.6 gpm

### Operating Temperature

40 to 100 °F (4.4 to 37.8 °C)\*

### Operating Pressure

30 -120 psi

### Change Frequency

6 to 12 months

### Capacity

1500 Gallons

### Materials of Construction

Filter Media: Granular Activated Carbon

\*Temperature ratings vary and depend on pressure and time under load

## Contaminants Reduced:

- Chlorine Taste and Odor
- Dirt
- Rust
- Sediment

Distributed

**neoLogic**  
solutions  
filtration division

2299 Ridge Rd., Greenville, SC  
P: 888.859.1188 · F: 864.284.1819  
[NeoLogicSolutions.com](http://NeoLogicSolutions.com) · [Info@NeoLogicSolutions.com](mailto:Info@NeoLogicSolutions.com)

## Questions?

Ask our Service Representatives at:  
888.859.1188 Mon.-Fri. 8a-8p,  
Sat 8:30a-4:30p EST.