

NP-3M704

SQC Compatible Replacement Cartridges



Component NP-3M704 is tested and certified by WQA to NSF/ANSI 372 and NSF/ANSI 42 for material safety and structural integrity requirements

Residential/Commercial Filtration Applications

Standard Features

- Manufactured in South Korea
- Compatible with the Water Factory Systems SQC3 and SQC4 systems
- Replacement for 47-55704G2, 47-557047CM, and PSQC-3*
- Reduces chlorine taste and odor, and sediment, dirt and rust
- NP-3M704 is tested and certified by WQA to NSF/ANSI 372 and NSF/ANSI 42 for material safety and structural integrity requirements

*Not tested by WQA in these systems

Product Specifications

Micron Rating (Nominal)

5 microns

Flow Rate

0.6 gpm

Operating Temperature

40 to 100 °F (4.4 to 37.8 °C)*

Operating Pressure

30 -120 psi

Change Frequency

6 to 12 months

Capacity

1500 Gallons

Materials of Construction

Filter Media: Granular Activated Carbon

*Temperature ratings vary and depend on pressure and time under load

Contaminants Reduced:

- Chlorine Taste and Odor
- Dirt
- Rust
- Sediment

Distributed

neoLogic
solutions
filtration division

2299 Ridge Rd., Greenville, SC
P: 888.859.1188 · F: 864.284.1819
NeoLogicSolutions.com · Info@NeoLogicSolutions.com

Questions?

Ask our Service Representatives at:
888.859.1188 Mon.-Fri. 8a-8p,
Sat 8:30a-4:30p EST.