

WATER FILTERS 11/01/19 Item # 13076

| Item #: ______ | Project: ______ | Qty: _____ | AIA#:

E-10 PREFILTER (9795-80)

E-20 PREFILTER (9795-90)



E-10 and E-20 Prefilters can be used for ice. Everpure prefilters are designed to increase the life of Hoshizaki 4HC-H water filters in areas with an unusual amount of dirt in the water. With a 10 micron (nominal) rating, the economical Everpure prefilter traps much of the dirt which contributes to scale buildup in ice makers, and clogs the delicate orifices of other water-using equiment.

twin and triple

configuration

When you install an Everpure prefilter, the Hoshizaki 4HC-H water filters can concentrate on what they do best: remove particles one (1) micron nominal and larger in size.

Replacement Cartridges:

E-10 Prefilters: 12 pack (9534-12)

single configuration

40 pack (9534-40)

E-20 Prefilters: 6 pack (9534-26)

20 pack (9534-20)







Warranty:

One Year replaceable elements*
One Year the entire system

* Warranty applies to material defects in materials & workmanship only.

Hoshizaki reserves the right to change specifications without notice.

H9320 FILTER Single, Double, Triple







H9320-51

Single Configuration

18.4" H

Double Configuration 19.11" H*

Triple Configuration 19.15" H*

HOSHIZAKI H9320 FILTER

Available in single, double and triple configurations. Rated NSF Class 1, STD 42, for taste, odor and chlorine reduction and for mechanical filtration (95.6% removal of particles one (1) micron and larger in size.)

- Keep ice makers functioning at full capacity
- 93.7% average reduction of chlorine from incoming water supply, eliminating tastes and odors of the ice
- Filters are rated as one (1) micron nominal producing crystal clear ice
- Decrease machine maintenance by reducing lime scale build-up

	Model	Filter	Max Flow Rate	Working Pressure	Temperature	Capacity
	H9320-51	4HC-H	2 gpm	10-125 psi	35-100°F	21,000 gal
	H9320-52	4HC-H	4 gpm	10-125 psi	35-100°F	42,000 gal
	H9320-53	4HC-H	6 gpm	10-125 psi	35-100°F	63,000 gal

Plumbing

Inlet/Outlet Connections: Single: (2) 3/8" FNPT

Double & Triple: (1) 3/4" MNPT / (1) 3/4" FNPT

The H9320 Filters and their respective cartridges have been tested and listed by NSF only for the functions listed above. Check for compliance with state and local laws and regulations. Do not use where the water is microbiologically unsafe, or with waters of unknown quality without adequate disinfection before or after the unit. The H9320 filter can be used with water that may contain filterable cysts.



The H9320 System is tested and certified by NSF International against NSF/ANSI Standard 42 for the reduction of:

Std. No. 42 - Aesthetic effects

Aesthetic Effects Mech

Bacteriostatic Effects
Chemical Reduction

Mechanical Filtration
Nominal Particulate Class 1

ral Reduction Taste & Odor

Chlorine

^{*}height includes manifold and cartridge



WATER FILTERS 11/01/19 Item # 13076

Model Number	Description Flow Rate (Gal. per min.)	Undercounter KMs	KM Cubers	IM Cubers	Cubelets & Flakers	DCM/DBs
H9320-51	Single (2 GPM)	AM-50 KM-81 KM-116 KM-161 KM-231 KM-301	KM-350, 520, 660 KML-325, 500, 700 KMD-410, 460, 530 KMS-830 DKM-500	IM-200, 500	All Models	All Models
H9320-52	Twin 2 x (2 GPM)	N/A	KM-901, 1100 KMD-860 KMS-822, 1122, 1402	N/A	N/A	N/A
H9320-53	Triple 3 x (2 GPM)	N/A	KM-1301, 1340, 1601, 1900, 2200, 2600 KMH-2100 KMS-2000	N/A	N/A	N/A
H9655-11	Replacement Cartridge (1) One each		er configurations based on average ic ons or higher usage, then it may be			our operation has





