SHARKBITE THE MARK OF QUALITY





LEAD-FREE/SAFETY*

All SharkBite® fittings are made of Lead Free DZR brass and exceed ASSE 1061 Section 1V, 4.1 Materials-Dezincification (DZR)-ISO 6509 standards.

*Reference Page 26 for additional information.

VERSATILE

SharkBite fittings have the versatility to transition from Copper, PEX, CPVC, PE-RT, HDPE, Polybutylene and PVC.



PROVEN AND GUARANTEED

SharkBite's quality and performance is field-proven with more than 550 million connections. SharkBite owns the entire manufacturing process, from raw brass to finished product, making SharkBite the only push-to-connect brand that can ensure a clean, leak-free connection.



NO TOOLS

No glue, solder, clamps or unions required when using SharkBite fittings, providing a quick and efficient application that saves installers time, labor, and money.



FLEXIBILITY

SharkBite fittings can be rotated even after assembly allowing for easier installation in tight places.



BEHIND-THE-WALL

SharkBite fittings are approved to be used underground and behind walls without access panels.

CERTIFICATIONS

- Fittings are certified to 200°F (93°C) max and 200 psi max
- Design certified to NSF/ANSI 61 and ASSE 1061 product standard for use in potable water and hydronic heating water distribution

SHARKBITE CONNECTION SYSTEM

REDEFINING EFFICIENCY

For more than 20 years and with over 250 million fittings installed, SharkBite has been at the forefront of innovating solutions for helping the plumbing trade improve efficiency with enhanced jobsite performance. Being a leader through continuous innovation and providing solutions that address the challenges that plumbing professionals face every day is who we are. Whether you are repairing a water line, installing a water heater, remodeling a home or plumbing a system in a new construction job, SharkBite provides proven solutions that save time, reduce cost, and have the versatility to overcome the most difficult situations.

TOTAL SYSTEM

The SharkBite system includes a wide range of plumbing fittings, valves, PEX pipe, outlet boxes and other plumbing accessories, making it the only system that is a total end-to-end plumbing solution from meter to fixture. This means compatibility and peace of mind quality that is backed by a single manufacturer.

www.sharkbite.com

All SharkBite fittings are made of Lead Free DZR brass and exceed ASSE 1061 Section 1V, 4.1 Materials-Dezincification (DZR) - ISO 6509 standards.





	PRODUCT DESCRIPTION	PART NUMBER	QTY/BAG
æ	1-1/4" X 1-1/4" (For PEX applications, stiffeners are sold separately)	UXL0535	1
LARGE DIAMETER	1-1/2" X 1-1/2" (For PEX applications, stiffeners are sold separately)	UXL0541	1
5	2" X 2" (For PEX applications, stiffeners are sold separately)	UXL0554	1
5°	STREET ELBOWS		
/2" x	: 1/2" CTS Tail Adapter (CTS end inserts into any 1/2" SB fitting)	U615LF	6
/4" x	: 3/4" CTS Tail Adapter (CTS end inserts into any 3/4" SB fitting)	U620LF	6
æ	1-1/4" X 1-1/4" (For PEX applications, stiffeners are sold separately)	UXL0735	1
DIAMETER	1-1/2" X 1-1/2" (For PEX applications, stiffeners are sold separately)	UXL0741	1
5	2" X 2" (For PEX applications, stiffeners are sold separately)	UXL0754	1
M	ALE ELBOWS		
'2" X	(1/2" FNPT	U308LF	6
ļ" X	(3/4" FNPT	U314LF	3
ALI	E ELBOWS		
2" X	(1/2" MNPT	U280LF	6
4" X	(3/4" MNPT	U286LF	6
Ð	JCING ELBOWS		
'2" X	(3/8" (1/2" OD)	U272LF	12
4" X	(1/2"	U274LF	6
X 3,	/4"	U278LF	3
RO	P-EAR ELBOWS		
B" (1/2" OD) X 1/2" FNPT	U332LF	6
2" X	(1/2"	U249LF	12
?" X	(1/2" FNPT	U334LF	6
! " X	(3/4" FNPT	U340LF	6
-E	AR EAR ELBOWS		
" X	(1/2" Hy-Ear	U335LF	6
SH	WASHER ELBOWS		
4" (3/8" OD) X 3/8" MNPT	U276LF	6
1/4" (3/8" OD) X 3/4" Garden Hose Nut		U2276LF	6
2" X	(3/8" MNPT	U281LF	6
ES			
4" (3/8" OD) X 1/4" (3/8" OD) X 1/4" (3/8" OD)	U358LF	6
'8" (1/2" OD) X 3/8" (1/2" OD) X 3/8" (1/2" OD)	U360LF	6
'2" X	(1/2" X 1/2"	U362LF	12
′4" X	(3/4" X 3/4"	U370LF	6
X 1'	"X 1"	U374LF	3
~	1-1/4" X 1-1/4" X 1-1/4"	UXL0835	1
DIAMETER	1-1/2" x 1-1/2" X 1-1/2"	UXL0841	1
2	2" X 2" X 2"	UXL0854	1
Dl	JCING TEES		
8" (1/2" OD) X 3/8" (1/2" OD) X 1/2"	U364LF	6
′2" X	(1/2" X 1/4" (3/8" OD)	U359LF	6
	(1/2" X 3/8" (1/2" OD)	U363LF	6

