



# CTOX Series

## Choramine Plus Carbon Block Filter Cartridges



### Residential/Commercial Filtration Applications

### Standard Features

- Manufactured in the USA
- Eco-friendly activated coconut shell carbon filter media to provide exceptional filtration and a high level of CTO, Lead, Chloramine, MTBE, VOC, and Cyst reduction
- Economical and competitive price while providing exceptional performance and high adsorptive capacity
- All materials and components are FDA compliant. Ideal for drinking water applications in residential, food service and commercial settings
- Filters available in standard 2-1/2" and 4-1/2" (BB-style) cartridge diameters
- Polypropylene outer netting and layers provide superior sediment and particulate reduction
- NSF/ANSI standard 42 certified for material requirements only
- Performance claims tested and verified by independent third party laboratory
- California Prop 65 Compliant

### Contaminants Reduced:

- Asbestos reduction\*
- Atrazine reduction\*
- Chlorine Taste and Odor\*
- Cyst reduction\*
- Lead reduction\*
- Lindane reduction\*
- Mercury reduction\*
- MTBE reduction\*
- Particulate I reduction\*
- VOC reduction\*



Tested and certified by NSF International against NSF/ANSI Standard 42 for materials requirements only.

### Product Specifications

#### Filter Media

Coconut shell carbon block

#### Micron Rating (Nominal)

0.5 micron

#### Cartridge Length

10" and 20"

#### Outside Diameters

2-1/2" and 4-1/2" OD

#### Operating Temperature

40° F - 125° F

#### Operating Pressure

20 psig - 125 psig

#### WARNING:


Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

\*Based on Manufacturer's testing

## Ordering Guide (Example: CTOX-4510)

PART NUMBER	NOMINAL DIMENSIONS	CHLORAMINE, LEAD & MERCURY, VOC & MTBE	MAXIMUM FLOW	NOMINAL MICRON RATING	INITIAL PRESSURE DROP (PSI)
CTOX-2510	2-1/2" x 10"	2,500	1 GPM (3.785 LPM)	0.5	< 10 PSI @ 0.75 GPM
CTOX-2520	2-1/2" x 20"	5,000	2 GPM (7.57 LPM)	0.5	< 10 PSI @ 1.5 GPM
CTOX-4510	4-1/2" x 10"	8,000	3 GPM (11.35 LPM)	0.5	< 7 PSI @ 2.5 GPM
CTOX-4520	4-1/2" x 20"	17,000	6 GPM (22.71 LPM)	0.5	< 6.5 PSI @ 5 GPM

## Dimensions



## Case Packs

DIMENSIONS	QUANTITY
2-1/2" x 10"	20
2-1/2" x 20"	20
4-1/2" x 10"	12
4-1/2" x 20"	6



**Filter Housings  
Selection Guide**  
[CLICK HERE](#)

Distributed By:



2299 Ridge Rd., Greenville, SC  
**P:** 888.859.1188 • **F:** 864.284.1819  
[NeoLogicSolutions.com](http://NeoLogicSolutions.com) • [Info@NeoLogicSolutions.com](mailto:Info@NeoLogicSolutions.com)

## Questions?

Ask our Service Representatives at:  
 888.859.1188 Mon.-Fri. 8a-8p,  
 Sat 8:30a-4:30p EST.