














THE INFORMATION CONTAINED HEREON IS PROPRIETARY AND CONFIDENTIAL TO AQUATEC WATER SYSTEMS, INC. AND SHALL NOT BE USED OR DISCLOSED IN WHOLE OR IN PART WITHOUT FIRST OBTAINING THE WRITTEN PERMISSION OF AQUATEC WATER SYSTEMS, INC.

REVISIONS				
REV	DESCRIPTION	DATE	DRAWN	APPROVED
A	ECD #2100, RELEASE FOR PRODUCTION	8/7/01	E.G.	
B	ECD #2589, ADD FITTINGS	9/6/02	E.G.	
C	ECD #2625, CHG DRAWING NUMBER	10/3/02	E.G.	
D	ECD #2655, ADD O-RING MTL	10/25/02	E.G.	
E	ECD #3058, ADD FITTINGS	9/30/03	E.G.	

 <p>QBS-553 (BUNA N O-RING) QBS-553-V (VITON O-RING) 3/8" HOSE BARB TO 3/4" QUICK DISCONNECT, STRAIGHT * NOT TO BE USED FOR FLOWS GREATER THAN 1.5 LPM</p>	 <p>QBS-554 (BUNA N O-RING) QBS-554-V (VITON O-RING) 1/2" HOSE BARB TO 3/4" QUICK DISCONNECT, STRAIGHT</p>	 <p>QBS-555 (BUNA N O-RING) QBS-555-V (VITON O-RING) 5/8" HOSE BARB TO 3/4" QUICK DISCONNECT, STRAIGHT</p>	 <p>QBS-556 (BUNA N O-RING) QBS-556-V (VITON O-RING) 3/4" HOSE BARB TO 3/4" QUICK DISCONNECT, STRAIGHT</p>	 <p>QTS-556 (BUNA N O-RING) QTS-556-V (VITON O-RING) 1/2" MALE QST THREAD TO 3/4" QUICK DISCONNECT, STRAIGHT</p>
 <p>QBE-553 (BUNA N O-RING) QBE-553-V (VITON O-RING) 3/8" HOSE BARB TO 3/4" QUICK DISCONNECT, ELBOW * NOT TO BE USED FOR FLOWS GREATER THAN 1.5 LPM</p>	 <p>QBE-554 (BUNA N O-RING) QBE-554-V (VITON O-RING) 1/2" HOSE BARB TO 3/4" QUICK DISCONNECT, ELBOW</p>	 <p>QBE-555 (BUNA N O-RING) QBE-555-V (VITON O-RING) 5/8" HOSE BARB TO 3/4" QUICK DISCONNECT, ELBOW</p>	 <p>QBE-556 (BUNA N O-RING) QBE-556-V (VITON O-RING) 3/4" HOSE BARB TO 3/4" QUICK DISCONNECT, ELBOW</p>	
 <p>QJE-553 (BUNA N O-RING) QJE-553-V (VITON O-RING) 3/8" JOHN GUEST TO 3/4" QUICK DISCONNECT, ELBOW</p>	 <p>QJE-554 (BUNA N O-RING) QJE-554-V (VITON O-RING) 1/2" JOHN GUEST TO 3/4" QUICK DISCONNECT, ELBOW</p>	 <p>QJS-553 (BUNA N O-RING) QJS-553-V (VITON O-RING) 3/8" JOHN GUEST TO 3/4" QUICK DISCONNECT, STRAIGHT</p>	 <p>QJS-554 (BUNA N O-RING) QJS-554-V (VITON O-RING) 1/2" JOHN GUEST TO 3/4" QUICK DISCONNECT, STRAIGHT</p>	

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES AT 65°F
TOLERANCES ARE:
FRACTIONS: DECIMALS: ANGLES:
±1/64 .x = .030 ±1/2°
.xx = .010
.xxx = .005
Ø CONCENTRICITY .005 T.I.R.
⊥ PERPENDICULARITY .0005/IN.
ANGULAR DIMS FOR CHAMF'S & C'SINKS ±2°
FILLET RADII .010 TO .030
BREAK CORNERS .005 TO .015 R. OR CHAMF.
FINISH AA 125 MICRO IN. PER ANSI B46.

MATERIAL

FINISH

APPROVALS DATE

DRAWN E.G. 8/7/01

DESIGNED

CHECKED

SHEET 1 OF 1

AQUATEC WATER SYSTEMS INC.
17422 Pullman St., Irvine, Ca. 92614

FITTINGS,
550 SERIES

SIZE B SCALE NONE PART/DWG NO. QXX-55X-X REV E

CAD# QXX-55X	
PRODUCT CODE	
NEXT ASSY	USED ON
APPLICATION	

GEOMETRIC SYMBOLS
PER ANSI-Y14.5

DO NOT SCALE DRAWING