



## OASIS® Point-Of-Use Counter Top Cooler Specifications

**Cold Water Reservoir:** Type 304 stainless steel. External copper refrigerant coil. Reservoir insulation is removable, molded, expanded bead polystyrene.

**Water Storage Reservoir:** Type 304 stainless steel. 2-1/2 gallon capacity.

**Drip Receptor:** Ruggedly molded ABS. Easily removable.

**Electrical:** 115 volts, 60 Hz. Compressor hp: 1/20. Full load amps: POU1CTK, 1.2 amps; POU1CTHS, 5.5 amps. 3-wire service cord and polarized plug furnished.

**Faucets:** Durable polypropylene. Self-closing type. Easy to operate.

**Refrigeration Unit:** Convection-cooled condenser. Internal spring mounted, hermetically sealed compressor with automatic overload protection. No lubrication is needed. Refrigerant is controlled by an accurately calibrated capillary tube.

**Capacity:** 45 six-ounce cups of piping hot water per hour. 1-3/8 quart storage tank.

**Net Weight:** POU1CTK, 40 lbs; POU1CTHS, 50 lbs.

Room Temp.	*G.P.H. 50°F Water	Approximate No. of 3 oz. Cups/Hour at 50°F Water
70°F	1.0	42
80°F	0.9	38
90°F	0.8	34
100°F	0.7	29

\*Air Conditioning and Refrigeration Institute Standard Rating Condition

Model POU1CTHS delivers 45 six-ounce cups of hot water per hour in addition to cold water.

Model POU1CTK supplies tepid water for cooking in addition to cold water.

**Dimensions:** 12" wide x 16-3/4" x deep x 17-1/2" high.

**Cold Water Thermostat:** Temperature is controlled by an adjustable thermostat, easily accessible.

**Limited 5-Year Warranty:** (Continental limits of the United States and Canada): Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample copy available upon request.

Components in these water coolers and dispenser are lead free as defined by the Safe Drinking Water Act Amendments of 1986, and the Lead Free Contamination Control Act of 1988.

Models covered by these specifications are Listed by Underwriters' Laboratories and Certified by Canadian Standards Association.

### EXPORT

**Export Model:** POU1CTHSY is also available, operable on 220-240 volts, 50-60 Hertz, having 1/20 hp compressor and requiring no transformers. UL and CSA not applicable to export models.

**Warranty:** One year on the sealed refrigeration system and most component parts. Four-year replacement parts contract on sealed refrigeration system. Detailed warranty certificate enclosed with each water cooler; sample copy available upon request.