Claris Medium Filter Cartridge

Adjustable ion-selective filters to tailor carbonate hardness levels in potable water



APPLICATIONS

The Claris filter systems are typically used to feed the following appliances:

Coffee and Espresso Machines

Hot drink vending machines

Combi steamers and self-cooking systems
Steam cookers and

Brewed Iced Tea

CARTRIDGE FEATURES

Five-stage filtration process:

- Prefiltration
- Carbonate hardness adjustment
- · Fine filtration
- Highly efficient carbon block removes harmful contaminants and unpleasant odors and tastes
- Solid membrane filter removes particles down to 5 micron for highest equipment protection

Operation in vertical or horizontal position.

NSF Certified under NSF/ANSI Standard 42.

OPERATIONAL TIPS

Change Claris cartridges when its pre-calculated water volume has been reached or at least once a year.

Change cartridges when capacity is reached.

Always flush the filter cartridge at time of installation and cartridge change.

Do not use hardness test strips to check for hardness reduction. Please use Titration kit to check for hardness reduction.

Everpure Claris water treatment systems (excluding replaceable elements) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. Everpure replaceable elements (filter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Everpure will provide a copy of the warranty upon request.



Claris Medium Filter Cartridge: EV4339-11

SPECIFICATIONS

Overall Dimensions: Service Flow Rate:

Pressure Requirements: Temperature:

Electrical Connection:

Treatment Capacity:

Medium (A)16.78" H x (B)3.74" W (426 x 95 mm) Medium 0.50 gpm (2 Lpm)

29 – 116 psi (2 – 8 bar), non-shock

39 - 86°F (4 - 30°C)

None

Rated for 660 gals. for Espresso applications and 790 gals. of OCS/Coffee applications. This capacity is based on influent water hardness of 180 ppm with standard bypass settings. For steam applications and other hardness levels consult installation and operations guide capacity and bypass settings charts.



Claris Medium Filter Systems

EV4339-11

INSTALLATION TIPS

The system can be operated freestanding, lying horizonally or mounted vertically.

If mounting vertically to a wall, securely connect the mounting backet to the wall using suitable screws.


Water pressure at the filter system inlet must not exceed 116 psi (8 bar). A pressure reducer valve must be installed on the water supply side of the filter system if the inlet pressure exceeds 116 psi (8 bar).

Shut off valve must be installed upstream of

Refer to Installation, Operation & Maintenance Manual for cartridge flushing and start-up.

The contaminants or other substances removed or reduced by this drinking water system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the systems. Systems certified for cyst reduction may be used with disinfected water that may

EVERPURE reserves the right to update specifications, change prices, or make substitutions without notice.





System Tested and Certified by NSF International against NSF/ANSI Standard 42 for the reduction of:

tandard No. 42 Aesthetic Effects Chemical Unit Taste and Odor Reduction Chlorine Reduction

Everpure-Shurflo India A-25 Mohan Co-operative Industrial Estate Mathura Road New Dehli, 110 044 INDIA TEL: 011.661.188.00 FAX: 011.661.188.22

contain filterable cysts.

Everpure-Shurflo Japan Inc. Hashimoto MN Bldg. 7F 3-25-1 Hashimoto, Midori-ku Sagamihara-Shi Kanagawa 252-0143 JAPAN

TEL: 81.(0)42.775.3011 FAX: 81.(0)42.775.3015



CHINA TEL: 86.21.3211.4588 FAX: 86.21.3211.4580



Visit our website at www.everpure.com

Pentair Filtration Solutions, LLC World Headquarters-Everpure/Shurflo North and South America Sales 1040 Muirfield Dr. Hanover Park, Illinois 60133 USA

TEL: 800.323.7873 (US only) TEL: 630.307.3000 FAX: 630.307.3030 Everpure-Shurflo Australia 2 Redwood Drive Notting Hill Victoria, 3168 AUSTRALIA TEL: 011.61.39.574.4000 FAX: 011.61.39.562.7237 Everpure-Shurflo Southeast Asia 18 Boon Lay Way #04-110/111 TradeHub 21, 609966 SINGAPORE TEL: 65.6795.2213 FAX: 65.6795.2219

Everpure-Shurflo Europe byba Industriepark Wolfstee Toekomstlaan 30 B-2200 Herentals BELGIUM TEL: +32.(0).14.283.500 FAX: +32.(0).14.283.505

EV4339-11 JE10