

**FOR CUSTOMERS
WHO DEMAND THE BEST**

HIS Water Filter

In-line filters are highly robust as they are under water pressure all of the time. They were originally designed to be fitted to the mains cold water pipe underneath the kitchen counter. In addition to being used in the home, FICL's in-line filters have proved very popular within the water cooler industry. They are easy to incorporate into cooler plumbing.

Made from high quality stainless steel, the HIS is a cost-effective and easy to use filter unit. It can be used either to filter all cold water running into the kitchen sink, or to provide filtered drinking water via a separate faucet. The HIS is available with either push-fit or BSP threaded connections.


Doulton[®]
world class ceramic filters


**British
Berkefeld**
world class ceramic filters



- 💧 Ideal for kitchen (under sink), water cooler, or water fountain installation.
- 💧 Up to 300 litres per hour of refreshingly clean drinking water on tap.
- 💧 Easy to install and use. Simple to maintain. Wholly reliable.
- 💧 No power required. Protecting you whether or not power is available.
- 💧 Fitted with long life, cleanable, ceramic filters giving you extra value.
- 💧 The HIS should be fitted with Sterasyl™, Carbosyl™, Supercarb™ or Ultracarb™ filter candles.
- 💧 Filters out:
 - 💧 Pathogenic Bacteria (cholera, typhoid, salmonella, E-coli, etc.).
 - 💧 Giardia, Cryptosporidium, and other chlorine resistant parasites.
 - 💧 Particles such as rust down to 0.5 microns in size.
 - 💧 Chlorine to improve taste and odour (when fitted with a Super-Sterasyl™, Supercarb™ or Ultracarb™ filter).
 - 💧 Harmful heavy metals such as lead (when fitted with an Ultracarb™ filter).



www.faireyceramics.com



Doulton's NSF certified products are only listed for specific claims against standard 42 and 53.

**HEALTHY WATER
HEALTHY LIFE**

Doulton
world class ceramic filters

**British
Berkefeld**
world class ceramic filters

- HIS is for use on all pressurised water supplies up to a maximum pressure of 100 psi.
- Should be fitted with any 10 inch long x 2 inch diameter Doulton® short mount filter candle.
- Ceramic filter candles can be cleaned to extend their life.
- The choice of filter candle grade depends on what you want to remove from your water:



| Technical Details | | |
|---------------------------|-------------------|-----------------------|
| Model | HIS | HIS Push Fit |
| Typical Output (SterasyI) | 300 (L/hr) | 300 (L/hr) |
| Max Operating Pressure | 100 psi | 100 psi |
| Max Operating Temperature | 38° c | 38° c |
| Connections | 1/2" BSP Parallel | 3/8" OD tube push fit |

| | SterasyI™ | Super SterasyI™ | Carbosyl™ | Super-carb™ | Ultracarb™ |
|---|-----------|-----------------|-----------|-------------|------------|
| Pathogenic bacteria, Cryptosporidium, Giardia, etc. | ✓ | ✓ | ✓ | ✓ | ✓ |
| Particles down to 0.5 microns (rust etc.) | ✓ | ✓ | ✓ | ✓ | ✓ |
| Chlorine (improve taste and odour) | ✗ | ✓ | ✓ | ✓ | ✓ |
| Organics | ✗ | ✓ | ✓ | ✓ | ✓ |
| Lead and heavy metals | ✗ | ✗ | ✗ | ✗ | ✓ |



www.faireyceramics.com



Doulton's NSF certified products are only listed for specific claims against standard 42 and 53.