

Acetal Half Cartridge

Pressure Ratings			
	< 5/16"	3/8"	1/2"
33 °F	290 psi	232 psi	203 psi
68 °F	290 psi	232 psi	203 psi
150 °F	232 psi	203 psi	116 psi

Torque Allowance					
Thread Size	1/8"	1/4"	3/8"	1/2"	3/4"
Max Torque	1.1 ft lbs	1.1 ft lbs	2.2 ft lbs	2.2 ft lbs	2.9 ft lbs

Model	ØA	B	ØD	ØE	ØF	ØG	H	I	J	WEIGHT(g)
HCAE-4M (HCAE-Z5)	11.85	5.0	12.0	8.3	4.15	3.3	4.9	8.9	12.8	0.8
HCAE-6M	13.30	4.6	13.40	10	6.15	5.3	4.6	9.8	14	0.9
HCAE-8M (HCAE-5)	13.70	5.6	13.80	11.95	8.15	7.4	5.5	10.15	15	1.1
HCAE-10M	15.90	6.9	16.05	14	10.15	9.2	6.9	11.8	18.2	1.4
HCAE-12M	19.60	7.9	19.75	16.55	12.15	11.2	7.75	15.9	23.9	2.6
HCAE-4	13.30	4.6	13.40	10.8	6.5	5.8	4.6	9.8	14.1	1
HCAE-6	15.90	6.9	16.05	13.9	9.65	8.9	6.85	11.8	18.2	1.6
HCAE-8	19.60	7.9	19.75	17.4	12.85	12.2	7.7	14.9	22.9	2.6

*replace HCAE with HCAB for parts with NBR o ring

