

**FATBOY SERIES PRODUCT TECHNICAL DATA SHEET**

OEM: 5518-111-94A  
 AFTERMARKET: 90-5518-111-94A-SB (Includes Fittings)

---

**APPLICATION:** Agricultural Chemical and Sprayer application intermittent duty only. This pump is not listed for potable water use.



**PUMP DESIGN:**

Type: 5 chamber, positive displacement diaphragm  
 Maximum Flow: 7.0 GPM [26.05 LPM]  
 Fluid Ports: 3/4" Quick Attach Female  
 Liquid Temp: 140 F [50 C]  
 Prime: 14 feet [4.2M]  
 Run Dry: Yes  
 Pressure Setting: 100 PSI [6.9Bar]  
 Label: Remco Label, Part #, Specs, Serial #, MFG date

**ELECTRICAL:**

Motor: 12 VDC Permanent Magnet, Intermittent duty, Sealed motor  
 Voltage Range: 11.5 VDC – 14.5 VDC  
 Max Amps: 24.5 Amps Max at 60 PSI  
 Leads: 12 AWG, 12" [30.48cm] leads  
 Fuse: 30 Amp Recommended  
 Control: Pressure switch  
 Max Temp: 180 F [82 C]  
 IP Rating: IP65

**MATERIALS OF CONSTRUCTION:**

Housings: Polypropylene  
 Valves: Viton  
 Diaphragm: Santoprene  
 Base: Welded  
 Hardware: Zinc plated screws

**AGENCY APPROVALS:**

CE, RoHS

**SHIPPING INFORMATION:**

Net Weight: 8 lbs  
 Carton Qty: 6  
 Carton Weight: 42 lbs  
 Carton Size: 6" x 22" x 17.75"

PSI	GPM	BAR	LPM	Amperage
0	7.00	0.00	26.50	10.00
10	6.80	0.69	25.74	12.00
20	6.45	1.38	24.42	13.00
30	5.90	2.07	22.33	14.00
40	5.50	2.76	20.82	15.00
50	4.95	3.45	18.74	17.00
60	4.40	4.14	16.66	19.00
70	3.95	4.83	14.95	21.00
80	3.50	5.52	13.25	22.50
90	3.05	6.21	11.55	23.50
100	2.55	6.90	9.65	24.50

## HEAT RISE 5518-111-94A

