



G/C Valves designs and manufactures world class solenoid valves to meet the rigors of today's most demanding applications.

These debris tolerant valves are manufactured from high strength, corrosion free, UV resistant nylon reinforced plastic. They feature a high flow, bypass handle for valve actuation in the case of power failure.

Features

- Class H (6.5 VA draw)
- Water tight sealed molded coil
- CE Certified
- 3-meter (118 in) length cord
- PVC jacketed Extension Cable
- 18/3 Wire Size

Specifications

Part Number	204908	204909	204910	204911	204912	204913	204914	204917	204918	204919	204920
End Connections FNPT (in)	1/2	1/2	1/2	3/4	3/4	1	1	1 1/2	1 1/2	2	2
Flow Range (gpm / lpm)	5 - 100 / 18.9 - 378	5 - 100 / 18.9 - 378	5 - 100 / 18.9 - 378	5 - 20 / 18.9 - 75.6	5 - 20 / 18.9 - 75.6	5 - 35 / 18.9 - 132.3	5 - 35 / 18.9 - 132.3	25 - 100 / 94.5 - 378.0	25 - 100 / 94.5 - 378.0	60 - 180 / 226.8 - 680.4	60 - 180 / 226.8 - 680.4
Voltage (V)	24	110	220	110	220	110	220	110	220	110	220
Minimum Operating Pressure (psi)	5			10							
Maximum Operating Pressure (psi)	100			125							

Engineered Water Treatment Solutions