

# NP-3MM100

## SQC RO Membrane Compatible Replacement Cartridges

**neo·PURE**<sup>®</sup>  
Filtration Products



Component  
NP-3MM100 is tested  
and certified by WQA  
to NSF/ANSI 372 and  
NSF/ANSI 58 for  
material safety and  
structural integrity  
requirements



### Residential/Commercial Filtration Applications

## Standard Features

- Manufactured in South Korea
- Formally NP-SQCM100
- Compatible with the Water Factory Systems SQC3 and SQC4 systems
- Replacement for 3MROM413, 66-4709G2, 66-4709CM, 66-4710G2, 66-4710CM\*
- Reduces chlorine taste and odor, and sediment, dirt, rust, cysts and VOCs
- Quick change design for easy installation
- NP-3MM100 is tested and certified by WQA to NSF/ANSI 372 and NSF/ANSI 58 for material safety and structural integrity requirements

\*Not tested by WQA in these systems

## Product Specifications

### Flow Rate

100 GPD

### Operating Temperature

34 to 100°F (4.4 to 37.8°C)\*

### Operating Pressure

30 -120 psi

### Change Frequency

24-36 months

### Capacity

2500 Gallons

### Materials of Construction

Filter Media: TFC (Thin Film Composite)

\*Temperature ratings vary and depend on pressure and time under load

## Contaminants Reduced:

- Chlorine Taste and Odor
- Dirt
- Rust
- Sediment
- Cysts
- VOCs

Distributed

**neoLogic**  
solutions  
filtration division

2299 Ridge Rd., Greenville, SC  
P: 888.859.1188 · F: 864.284.1819  
[NeoLogicSolutions.com](http://NeoLogicSolutions.com) · [Info@NeoLogicSolutions.com](mailto:Info@NeoLogicSolutions.com)

## Questions?

Ask our Service Representatives at:  
888.859.1188 Mon.-Fri. 8a-8p,  
Sat 8:30a-4:30p EST.