

## Model RVF-10

The sturdy design of model RVF-10 makes it ideal for exterior pre-tank filtration of water for the RV. This unit provides better-tasting water for drinking and cooking, and its sediment filtration ability ensures a cleaner storage tank, too. The slim design and convenient hose fitting kit make it simple to install and easy to store.

### Package Includes:

- Filter housing
- D-15 replacement cartridge
- Hose and fittings
- Installation instructions
- Filter change reminder sticker

### Replacement Parts:

- D-15
- OR-38



OR-38



D-15

### System Requirements:

- Water pressure of 30-125 psi (2.1-8.6 bar)
- Water temperature of 40-100° F (4.4-37.8° C)

## Models RV-500A, RV-600A, RV-700 & RV-800

Convenient and easy to use, model RV-600A and RV-800 is a disposable exterior pre-tank filter for drinking and cooking water. It also filters dirt and sediment to keep the storage tank clean and clear. For use with 3/4-inch flexible hose couplings in RV or marine applications, the RV-600A and RV-800 provides a high flow rate for quick tank fills. Models RV-500A and RV-700 includes the filter cartridge only (no hose).

### Package Includes:

#### RV-500A / RV-600A

- Plastic plugs
- Hose (RV-600A only)
- Installation instructions
- Filter change reminder sticker
- Granular activated carbon filter

#### RV-700 / RV-800

- Plastic plugs
- Hose (RV-800 only)
- Installation instructions
- Filter change reminder sticker
- Granular activated carbon filter

## Contact information:

### Customer Service:

M-F 8:00 a.m. – 4:30 p.m. CST  
 Phone: 1-800-721-7360  
 Fax: 1-800-721-7390  
 International Phone: 1-920-457-2726  
 International Fax: 1-920-457-7366

### Sales & Marketing Correspondence

P.O. Box 1086  
 Sheboygan, WI 53082-1086  
 Phone: 1-877-864-1484  
 Fax: 1-920-457-7366  
 Email: sales-marketing@culligan.com

Culligan International  
 Rosemont, Illinois 60018  
 www.culligan.com

**WARNING:** do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

- This device must be maintained according to manufacturer instructions including replacement of filter cartridges.
- Read all precautions on box and in manual before installing and using this system.



## RV-500A, RV-600A, RV-700 & RV-800

Tested and Certified by NSF International to NSF/ANSI Standard 42 for the aesthetic reduction of Chlorine Taste and Odor.

### Individual Unit & Case

MODEL #	LEVEL	UNIT WT	UNIT DIMS H" x W" x D"	CASE QTY	CASE WT (LBS)	CASE DIMS L" x W" x D"	CASE CU FT	CASE UPC
RV-500A	Level 1	1.19	11.5 x 4.25 x 2.75	6	8.0	9.25 x 9.25 x 12.25	.11	1 00 33663 00515 7
RV-600A	Level 1	1.41	11.5 x 4.25 x 2.75	6	9.0	9.25 x 9.25 x 12.25	.11	1 00 33663 00516 4
RV-700	Level 1	1.44	11.5 x 4.25 x 2.75	6	9.0	9.25 x 9.25 x 12.25	.11	1 00 33663 00655 0
RV-800	Level 1	1.72	11.5 x 4.25 x 2.75	6	11.0	9.25 x 9.25 x 12.25	.11	1 00 33663 00656 7
RVF-10	-	2.75	12.5 x 4.75 x 4.75	6	17.0	15.25 x 10.25 x 13.0	1.18	5 00 33663 00549 5

### Replacement Parts & Accessories

MODEL #	LEVEL	UNIT WT	UNIT DIMS H" x W" x D"	CASE QTY	CASE WT (LBS)	CASE DIMS L" x W" x D"	CASE CU FT	CASE UPC
D-15	Level 1	0.71	9.75 x 4.25 x 2.25	6 (pair)	5.0	15.75 x 5.5 x 10.25	.51	7 00 33663 00567 8
OR-38	-	0.03	6.75 x 4.0 x .25	6	0.16	9.5 x 6.5	Envelope	1 00 33663 00507 2