

# Watts® ROs with Kwik-Change™ Cartridges

Simply the “best” of the “best”!

Internal valve shuts-off flow during cartridge and membrane replacement.

Hinge bracket for easy cartridge removal and replacement.

Cartridge replacement is so easy, you or the homeowner can do it!

Proprietary filter cartridges and membranes are installed and removed by a simple 1/4 turn.

Cartridges have double o-rings to prevent leakage.



WQA Gold Seal  
Certified to  
NSF / ANSI  
Std. 58



Watts® Kwik-Change™ Systems are designed for consumers that demand the “best”. Unlike conventional reverse osmosis systems, Watts drinking water systems with Kwik-Change cartridges have no sumps, so their proprietary filter elements and membranes are easy to replace.

### Full Product Line Available, Including:

50 Gpd Models • 100 Gpd Models • Metal Tanks  
Plastic Tanks • op Mount Faucets • Standard Faucets  
Models For Coolers • Custom Systems  
Drinking Water Systems With Filter Elements  
& Hollow Fiber Membranes.

## Features & Benefits

- Cartridges are connected and removed with a simple 1/4 turn.
- No filter sumps! No fuss! No mess!
- Automatic shut-off when cartridges are removed.
- Tank and faucet options available.
- Valves are built into the heads to prevent back-flow for water quality assurance.
- WQA Gold Seal Certified to NSF/ANSI Std. 58.



Watts® top mount faucets are mounted from above the counter top.



Long reach chrome faucet. Standard with all models listed on reverse.



Metal storage tank



RO Pro® Storage Tanks Only 9” wide, takes less space and won’t chip, rust or dent!

**Watts® Kwik-Change RO systems are so easy to service  
you'll get great quality water every time!**



### Conventional RO Systems

Conventional RO systems may provide high quality water. However, cartridges and membranes are difficult to replace because they are installed in housings and must be removed. This procedure includes the need to shut off and drain down the system, open the housings with a wrench, remove cartridges, empty water from the sumps, clean the filter and membrane housings, replace cartridges, re-pressurize, and check for leaks.

Because conventional systems are difficult to service, routine maintenance may be delayed. Therefore, consumers may not get the quality water they desire, unless a qualified dealer is called to service their system.



**VS.**

### Kwik-Change RO System

***No Sumps! No Mess! No Fuss!***

- Hinge bracket for easy handling.
- Automatic shut off when cartridges are removed with a simple, 1/4 turn.
- No need to disconnect tubing when replacing membranes.
- Integrated check valves between cartridges and membrane prevent back-flow.
- Cartridges have double o-rings so they will not leak.
- Quick connect fittings for easy installation.



**Watts Water Quality & Conditioning Products**

800-659-8400 (press 2 for sales)

Email: [wqp@watts.com](mailto:wqp@watts.com)

[watts.com](http://watts.com)

© Watts 2008

SS-WQP-KWCHG-0839