



- **5 Year Limited Warranty**
- **Butyl/EPDM Diaphragm**
- **Poly Liner**
- **Rubber Air Stem**
- **NSF Standard 61 Listed**
- **90 PSIG Maximum Working Pressure**
- **Helium Tested**

VALUE-WELLTM
PRE-PRESSURIZED WATER SYSTEM TANKS

VALUE-WELL economical



Value Well Specifications

| Model No. | Volume | Precharge | Maximum Acceptance Factor | System Drawdown | | | Dimensions | |
|-----------|-------------|-----------|---------------------------|-----------------|-------|-------|------------|--------|
| | | | | 20/40 | 30/50 | 40/60 | Diameter | Height |
| VW 20 | 20 Gallons | 38 PSIG | 0.57 | 8.0 | 6.8 | 5.9 | 15 | 32 |
| VW 32 | 32 Gallons | 38 PSIG | 0.35 | * | 10.9 | 9.4 | 15 | 48 |
| VW 44 | 44 Gallons | 38 PSIG | 0.77 | 17.7 | 15.0 | 13.0 | 22 | 30 |
| VW 62 | 62 Gallons | 38 PSIG | 0.55 | 32.6 | 27.5 | 18.3 | 22 | 36 |
| VW 86 | 86 Gallons | 38 PSIG | 0.54 | 34.6 | 29.2 | 25.4 | 26 | 47 |
| VW 119 | 119 Gallons | 38 PSIG | 0.39 | 47.8 | 40.5 | 35.1 | 26 | 62 |

For models VW20 and VW32, the system connection is 1" NPTF, 200 (degree Fahrenheit) maximum working temp. All other models, system connection is 1-1/4" NPTF, 200 (degree Fahrenheit) maximum working temp. Drawdown is the amount of water delivered by the tank between pump shut-down and pump start-up, and can be affected by various ambient and system conditions including temperature and pressure.

*Not Recommended

Tank Selector Guide

Match the number of fixtures in the home with the correct model

| Model Number | Fixtures |
|--------------|----------|
| VW 20 | 7 |
| VW 32 | 11 |
| VW 44 | 15 |
| VW 62 | 21 |
| VW 86 | 29 |
| VW 119 | 40 |

To convert a standard epoxy or galvanized tank to a Value-Well tank use the chart below

| Model Number | Epoxy/Galvanized Equivalents |
|--------------|------------------------------|
| VW 20 | 42 |
| VW 32 | 82 |
| VW 44 | 120 |
| VW 62 | 160 |
| VW 86 | 220 |
| VW 119 | 315 |

Ask for Quality. Ask for AMTROL®.

*Refer to installation manual for warranty information or visit our website at www.amtrol.com



Corporate Headquarters
 1400 Division Road, West Warwick, RI USA 02893
 Telephone: 401-884-6300 • Fax: 401-884-5276
 AMTROL Canada, Ltd.
 275 Shoemaker Street, Kitchener, Ontario N2E 3B3
 Telephone: 519-478-1138 • Fax: 519-748-4231



AMTROL, AT logo and Value-Well are registered trademarks of AMTROL Inc. and its affiliates in the U.S. and elsewhere. All rights reserved.

9040-539 (02/10) MC# 7010

©2010 AMTROL Inc.
 Printed in USA