

Tee Union

YOUR PLUMBING'S BEST CONNECTION

neofit

www.neologicsolutions.com

Pressure Ratings			
	< 5/16"	3/8"	1/2"
33 °F	290 psi	232 psi	203 psi
68 °F	290 psi	232 psi	203 psi
150 °F	232 psi	203 psi	116 psi

Model	ØD1	ØD2	B1	B2	ØE1	ØE2	H	L	WEIGHT(g)
ATUZ5Z5Z5	5/32	5/32	0.579	0.579	0.520	0.520	0.965	1.409	5.7
ATU333	3/16	3/16	0.591	0.591	0.543	0.543	1.004	1.465	6.2
ATU444	1/4	1/4	0.665	0.665	0.610	0.610	1.134	1.654	8.1
ATU555	5/16	5/16	0.689	0.689	0.693	0.693	1.209	1.724	10.6
ATU68M6	3/8	Ø8	0.795	0.689	0.787	0.787	1.398	2.039	16.1
ATU610M6	3/8	10	0.795	0.791	0.787	0.787	1.409	2.039	13.7
ATU646	3/8	1/4	0.795	0.665	0.787	0.591	1.264	1.921	12.2
ATU666	3/8	3/8	0.795	0.795	0.787	0.787	1.413	2.039	15.4
ATU868	1/2	3/8	0.969	0.795	0.906	0.906	1.677	2.512	25.3
ATU888	1/2	1/2	0.988	0.988	0.906	0.906	1.709	2.512	23.2

