

# HEPP200-X

## High Efficiency Permeate Pump



## Residential / Commercial Filtration Applications

### STANDARD FEATURES

- Quietest permeate pump in the industry
- Compact size
- Reduces the amount of water drained from RO systems, increasing their efficiency up to 85%
- Maintains highest quality water produced by the membrane significantly reducing TDS creep
- Extends the life of the membrane
- The pump operates by using the brine flow to drain. No electricity needed
- Compatible with RO systems with capacities up to 200 GPD

### PRODUCT SPECIFICATIONS



**Max Flow Rate**  
0.035 - 0.5 gpm



**RO Membrane Capacity**  
<200 gpd  
**Production Capacity**  
132,000 gal (500,000 L)



**Min Inlet Water Pressure**  
30psi (2 bar)

**Max Pressure**  
80psi (5.5 bar)

#### Product Dimensions

- Pump Diameter: 3.28"
- Pump Depth: 3.34"
- Pump Height (with clip): 3.7"



## QUESTIONS?

Ask our Service Representatives at:

888.859.1188

Mon. - Fri. 8a - 8p

Sat 8:30a - 4:30p EST.

Neologic Inc. | Greenville SC | Salt Lake City UT | Houston TX

All rights and illustrations reserved. Manufacturer reserves the right to make changes without notice. ©2018 NeoLogic Solutions.

#### WARNING:

Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.