

5200



When it's time for five-chamber performance, the 5200 is ready for your RV water system.



Typical Applications

Water Treatment/RO
 Agricultural Spraying
 General Industrial
 Automotive
 RV and Coach water pumps



An economical workhorse, the 5200 was engineered for flexibility. With on-demand switching, 3.0 to 5.0 GPM, and 60 PSI, the 5200 will meet your special requirements with positive predictable performance. Remco also offers a variety of Easy Connect fittings and filters.



Positive displacement pump



Can run dry



Quiet operation



Demand Pump



Easy connect fittings



Industry standard mount pattern

PUMP

Type

5 chamber positive displacement diaphragm pump, self priming, capable of being run dry

Mode

Demand

Liquid Temperature

140 degrees F

Priming Capabilities

up to 6 ft

Max Pressure

100 PSI (6.8 bar)

Inlet/Outlet Ports

1/2" MNPT

Weight

7 lbs (3.17 kg)

MOTOR

Leads

18 AWG, 4.5" long with 2-pin connector

Duty Cycle

Intermittent

STANDARD PUMP CONFIGURATIONS



| Model | Volt(V) | Switch | GPM/LPM | PSI/BAR | Max Draw (A) | Valves | Diaphragm | Ports | Lead Wire | Molded Connector |
|--------------|---------|--------|---------|---------|--------------|--------|------------|----------|-----------|------------------|
| 5264-1E1-80A | 12V | Demand | 3/11.3 | 60/4.1 | 10 | Viton | Santoprene | 1/2 MNPT | — | 2-Pin |
| 5266-1E1-80A | 12V | Demand | 4/15.1 | 60/4.1 | 12 | Viton | Santoprene | 1/2 MNPT | — | 2-Pin |
| 5267-1E1-80A | 12V | Demand | 5/18.9 | 60/4.1 | 15 | Viton | Santoprene | 1/2 MNPT | — | 2-Pin |

PERFORMANCE

5264 - 3.0 GPM

| PSI | Bar | GPM | LPM | Amps |
|------|------|------|-------|------|
| OPEN | 0 | 3.20 | 12.35 | 6.20 |
| 10 | 0.68 | 2.92 | 11.27 | 8.00 |
| 20 | 1.36 | 2.55 | 9.84 | 9.10 |
| 30 | 2.04 | 2.17 | 8.38 | 10.1 |
| 40 | 2.72 | 1.89 | 7.38 | 11.1 |
| 50 | 3.40 | 1.61 | 6.21 | 12.0 |
| 60 | 4.08 | off | 0 | 0 |

5267 - 5.0 GPM

| PSI | Bar | GPM | LPM | Amps |
|------|------|------|-------|------|
| OPEN | 0 | 5.10 | 19.7 | 9.60 |
| 10 | 0.68 | 4.20 | 16.21 | 11.4 |
| 20 | 1.36 | 3.52 | 13.59 | 12.7 |
| 30 | 2.04 | 3.05 | 11.77 | 14.2 |
| 40 | 2.72 | 2.61 | 10.07 | 15.4 |
| 50 | 3.40 | 2.24 | 8.65 | 16.3 |
| 60 | 4.08 | off | 0 | 0 |

5266 - 4.0 GPM

| PSI | Bar | GPM | LPM | Amps |
|------|------|------|-------|------|
| OPEN | 0 | 4.00 | 15.44 | 6.60 |
| 10 | 0.68 | 3.72 | 14.36 | 8.00 |
| 20 | 1.36 | 3.45 | 13.32 | 9.30 |
| 30 | 2.04 | 3.01 | 11.62 | 10.2 |
| 40 | 2.72 | 2.89 | 11.18 | 11.4 |
| 50 | 3.40 | 1.93 | 7.45 | 12.6 |
| 60 | 4.08 | off | 0 | 0 |



10546 Filter



QTS-332-12 Fitting



QTE-332-12 Fitting

FITTINGS

| Item Number | Size | Fitting Type | Material |
|-------------|----------------|---------------------------|----------|
| QTE-332-12 | 1/2 MNPT x 1/2 | HSE Barb Elbow Fitting | Nylon |
| QTS-332-12 | 1/2 MNPT x 1/2 | HSE Barb Straight Fitting | Nylon |

FILTER

| Item Number | Inlet | Outlet | Mesh Size |
|-------------|-----------|----------------------------------|-----------|
| 10546 | 1/2" MNPT | 1/2" FMPT Inline Filter/Strainer | 50 |

Fittings and filter included with pump.

