

Flow-Max[®] Phenolic Cellulose Cartridges

Ideal for high temperature industrial water and oil filtration.



Specifications

Maximum temperature	250°F (121°C)
Minimum temperature	-20°F (-29°C)
Maximum pressure	70 PSID (482 k PA)
Recommended change out	25 PSID (172 k PA)
End caps, cores, outer body	Electro plated tin
Media	Phenolic impregnated cellulose

Standard 2-1/2" OD x 9-3/4" Length With Electro Tin Plated Outer Body

Part Number	OD	Length	Micron	No. / case
FMPIC-5-975	2-1/2"	9-3/4"	5	30
FMPIC-20-975	2-1/2"	9-3/4"	20	30
FMPIC-50-975	2-1/2"	9-3/4"	50	30

Jumbo Model 40 (7-3/4" x 9-5/8")

Part Number	OD	Length	Micron	No. / case
FMPIC-40-5-HT	7-3/4"	9-5/8"	5	1
FMPIC-40-20-HT	7-3/4"	9-5/8"	20	1
FMPIC-40-50-HT	7-3/4"	9-5/8"	50	1

Jumbo Model 90 (7-3/4" x 19-1/2")

Part Number	OD	Length	Micron	No. / case
FMPIC-90-5-HT	7-3/4"	19-1/2"	5	1
FMPIC-90-20-HT	7-3/4"	19-1/2"	20	1
FMPIC-90-50-HT	7-3/4"	19-1/2"	50	1

Jumbo Model 170 (7-3/4" x 30-3/4")

Part Number	OD	Length	Micron	No. / case
FMPIC-170-5-HT	7-3/4"	30-3/4"	5	1
FMPIC-170-20-HT	7-3/4"	30-3/4"	20	1
FMPIC-170-50-HT	7-3/4"	30-3/4"	50	1

Note: Phenolic impregnated cellulose cartridges are not to be used for potable water. Jumbo cartridges fit in Flow-Max jumbo housings only.