

# 780 Softening Cartridge

## Softening cartridge reduces scale-forming minerals



7SO Replacement Cartridge: EV9707-04

EV9607-04

#### BENEFITS

Softening cartridge reduces hardness in water that can cause minerals to build-up in coffee and espresso equipment

Reduces minerals such as calcium and magnesium

May be used on water having up to 30 grains hardness per gallon (500 mg/L) at flow rates of up to 1/2 gallon per minute

Fits all existing Everpure heads. Recommended use as second cartridge in QC Twin Series configuration head (EV9272-24). Properly sized precoat filter cartridge should be installed before 7SO cartridge for best results

Sanitary cartridge replacement is simple, quick and clean. Internal filter parts are never exposed to handling or contamination

#### INSTALLATION TIPS

Choose mounting location suitable to support the full weight of the system when operating

Use 3/8" water line

Install vertically with cartridge hanging down

Allow 2-1/2" clearance below the cartridge for easy cartridge replacement

Flush 7SO cartridge by running water through filter for five minutes at full flow

### OPERATION TIPS

Change cartridges on a regular 6 month preventative maintenance program

Change cartridges when hardness of treated water increases to more than 3 gpm

Do not exceed recommended service flow rate

Always flush the filter cartridge at time of installation and cartridge change

#### APPLICATION/SIZING

For specialty coffee, espresso and ice tea applications

Capacity: 2,000 grains softening

Cartridge Grain Capacity divided by Grains Per Gallon In Influent Water = Total Product Water

# SPECIFICATIONS

Overall Dimensions: 20.75"H x 3.25"Diameter

Service Flow Rate: Maximum 0.5 gpm (1.9 Lpm)


Pressure Requirements: 10 - 125 psi (0.7 – 8.6 bar), non-shock

Temperature: 35 - 100°F (2 - 38°C)

No electrical connection required

The contaminants or other substances removed or reduced by this drinking water system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used with disinfected water that may contain filterable cysts.

# 780 Softening Cartridge



### WARRANTY

Everpure water treatment systems (excluding replaceable elements) are covered by a limited warranty against defects in material and workmanship for a period of five years after date of purchase. Everpure replaceable elements (filter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Everpure will provide a copy of the warranty upon request.

Worldwide Headquarters: EVERPURE, LLC 1040 Muirfield Drive Hanover Park, Illinois 60133 Toll Free (800) 323-7873 Tel (630) 307-3000 Fax (630) 307-3030 http://www.everpure.com In Europe:
Pentair Water Belgium B.V./B.A.
Industriepark Wolfstee
Toekomstlaan 30
B-2200 Herentals
BELGIUM
TEL: +32.(0).14.283.500

TEL: +32.(0).14.283.500 FAX: +32.(0).14.283.505 In Japan:
Hashimoto MN Bldg. 7F
3-25-1 Hashimoto Sagamihara-Shi Kanagawa 229-1103 JAPAN
TEL: 81.(0)42.775.3011
FAX: 81.(0)42.775.3015